

114CNC  
Legacy™ Line Air Conditioner for Coastal Applications  
with Puron® Refrigerant  
1–1/2 To 5 Nominal Tons



## Product Data



**COASTGUARD™**

**LEGACY™  
LINE**

Bryant heat pumps with Puron® refrigerant provide a collection of features unmatched by any other family of equipment. The 114CNC has been designed utilizing Bryant's Puron refrigerant. The environmentally sound refrigerant allows consumers to make a responsible decision in the protection of the earth's ozone layer.

**NOTE: Ratings contained in this document are subject to change at any time. Always refer to the AHRI directory ([www.ahridirectory.org](http://www.ahridirectory.org)) for the most up-to-date ratings information.**

### INDUSTRY LEADING FEATURES / BENEFITS

#### Efficiency

- 14.0 SEER / 11.0 – 13.5 EER
- Microtube Technology™ refrigeration system
- Indoor air quality accessories available

#### Reliability

- Puron® refrigerant
- Scroll compressor
- Internal pressure relief valve
- Internal thermal overload
- Filter drier

#### Durability

DuraGuard™ protection package:

- Solid, durable sheet metal construction
- Coastal coated dense wire coil guard
- Coastal coated fan guard
- Baked-on powder paint on all sides

CoastGuard™ Condenser Coil:

- Aluminum fin material is pre-coated on both sides with a corrosion protective epoxy phenolic coating.

#### Applications

- Long-line – up to 250 feet (76.20 m) total equivalent length, up to 200 feet (60.96 m) condenser above evaporator, or up to 80 ft. (24.38 m) evaporator above condenser with accessories. (See Residential Piping and Longline Guideline for more information.)
- Low ambient (down to –20°F/–28.9°C) with accessory kit

# PRODUCT NUMBER NOMENCLATURE

1	2	3	4	5	6	7	8	9	10	11	12	14
N	N	N	A	A/N	N	N	N	N	A/N	A/N	N	A
1	1	4	C	N	C	0	3	6	0	0	0	0
Product Family	Tier	SEER	Major Series	Voltage	Grille Variations	Cooling Capacity		Open	Open	Open	Minor Series	
1=AC	1= Legacy	4=14 SEER	C=Puron	N=208/230-1 P=208/230-3 E=460/3	C = Coastal	1,000 Nominal Btuh		0=Not Defined	0=Not Defined	0=Not Defined	A = Original Series	



Use of the AHRI Certified TM Mark indicates a manufacturer's participation in the program. For verification of certification for individual products, go to [www.ahridirectory.org](http://www.ahridirectory.org).

## PHYSICAL DATA

UNIT SIZE – SERIES	18-A	24-A	30-A	36-A	42-A	48-A	60-A
<b>Compressor Type</b>	Scroll						
<b>REFRIGERANT</b>	Puron® (R-410A)						
Charge lb (kg)	4.00 (1.81)	6.30 (2.86)	7.07 (3.21)	6.77 (3.07)	8.07 (3.66)	9.92 (4.50)	13.20 (5.99)
<b>COND FAN</b>	Propeller Type, Direct Drive						
Air Discharge	Vertical						
Air Qty (CFM)	1792	2200	2600	2600	3937	3600	4209
Motor HP	1/12	1/12	1/10	1/10	1/4	1/4	1/4
Motor RPM	1100	850	1100	1100	1100	1100	800
<b>COND COIL</b>							
Face Area (Sq ft)	9.8	15.1	12.9	12.9	15.1	19.4	25.1
Fins per In.	20	20	20	20	20	20	20
Rows	1	1	2	2	2	2	2
Circuits	3	4	5	5	6	7	10
<b>VALVE CONNECT. (In. ID)</b>							
Vapor	3/4	3/4	3/4	7/8	7/8	7/8	7/8
Liquid	3/8						
<b>REFRIGERANT TUBES (In. OD)</b>							
Rated Vapor*	3/4	3/4	3/4	7/8	7/8	7/8	1-1/8
Max Liquid Line†	3/8						

\* Units are rated with 25 ft (7.6 m) of lineset length. See Vapor Line Sizing and Cooling Capacity Loss table when using other sizes and lengths of lineset.

**Note:** See unit Installation Instruction for proper installation.

† See *Liquid Line Sizing For Cooling Only Systems with Puron Refrigerant* tables.

# REFRIGERANT PIPING LENGTH LIMITATIONS

## Liquid Line Sizing and Maximum Total Equivalent Lengths† for Cooling Only Systems with Puron® Refrigerant:

The maximum allowable length of a residential split system depends on the liquid line diameter and vertical separation between indoor and outdoor units.

See Table below for liquid line sizing and maximum lengths :

### Maximum Total Equivalent Length Outdoor Unit BELOW Indoor Unit

Size	Liquid Line Connection	Liquid Line Diam. w/ TXV	AC with Puron Refrigerant Maximum Total Equivalent Length†: Outdoor unit BELOW Indoor Vertical Separation ft (m)								
			0-5 (0-1.5)	6-10 (1.8-3.0)	11-20 (3.4-6.1)	21-30 (6.4-9.1)	31-40 (9.4-12.2)	41-50 (12.5-15.2)	51-60 (15.5-18.3)	61-70 (18.6-21.3)	71-80 (21.6-24.4)
18000 AC with Puron	3/8	1/4	150	150	125	100	100	75	--	--	--
		5/16	250*	250*	250*	250*	250*	250*	250*	225*	150
		3/8	250*	250*	250*	250*	250*	250*	250*	250*	250*
24000 AC with Puron	3/8	1/4	75	75	75	50	50	--	--	--	--
		5/16	250*	250*	250*	250*	250*	225*	175	125	100
		3/8	250*	250*	250*	250*	250*	250*	250*	250*	250*
30000 AC with Puron	3/8	1/4	30	--	--	--	--	--	--	--	--
		5/16	175	225*	200	175	125	100	75	--	--
		3/8	250*	250*	250*	250*	250*	250*	250*	250*	250*
36000 AC with Puron	3/8	5/16	175	150	150	100	100	100	75	--	--
		3/8	250*	250*	250*	250*	250*	250*	250*	250*	250*
42000 AC with Puron	3/8	5/16	125	100	100	75	75	50	--	--	--
		3/8	250*	250*	250*	250*	250*	250*	250*	250*	150
48000 AC with Puron	3/8	3/8	250*	250*	250*	250*	250*	250*	230	160	--
60000 AC with Puron	3/8	3/8	250*	250*	250*	225*	190	150	110	--	--

\* Maximum actual length not to exceed 200 ft (61 m)

† Total equivalent length accounts for losses due to elbows or fitting. See the Residential Piping and Long Line Guideline for details.

-- = outside acceptable range

### Maximum Total Equivalent Length Outdoor Unit ABOVE Indoor Unit

Size	Liquid Line Connection	Liquid Line Diam. w/ TXV	AC with Puron Refrigerant Maximum Total Equivalent Length†: Outdoor unit ABOVE Indoor Vertical Separation ft (m)								
			25 (7.6)	26-50 (7.9-15.2)	51-75 (15.5-22.9)	76-100 (23.2-30.5)	101-125 (30.8-38.1)	126-150 (38.4-45.7)	151-175 (46.0-53.3)	176-200 (53.6-61.0)	
18000 AC with Puron	3/8	1/4	175	250*	250*	250*	250*	250*	250*	250*	250*
		5/16	250*	250*	250*	250*	250*	250*	250*	250*	250*
		3/8	250*	250*	250*	250*	250*	250*	250*	250*	250*
24000 AC with Puron	3/8	1/4	100	125	175	200	225*	250*	250*	250*	250*
		5/16	250*	250*	250*	250*	250*	250*	250*	250*	250*
		3/8	250*	250*	250*	250*	250*	250*	250*	250*	250*
30000 AC with Puron	3/8	1/4	30	--	--	--	--	--	--	--	--
		5/16	250*	250*	250*	250*	250*	250*	250*	250*	250*
36000 AC with Puron	3/8	3/8	250*	250*	250*	250*	250*	250*	250*	250*	250*
		5/16	225*	250*	250*	250*	250*	250*	250*	250*	250*
42000 AC with Puron	3/8	5/16	175	200	250*	250*	250*	250*	250*	250*	250*
		3/8	250*	250*	250*	250*	250*	250*	250*	250*	250*
48000 AC with Puron	3/8	3/8	250*	250*	250*	250*	250*	250*	250*	250*	
60000 AC with Puron	3/8	3/8	250*	250*	250*	250*	250*	250*	250*	250*	

\* Maximum actual length not to exceed 200 ft (61 m)

† Total equivalent length accounts for losses due to elbows or fitting. See the Residential Piping and Long Line Guideline for details.

-- = outside acceptable range

## REFRIGERANT CHARGE ADJUSTMENTS

Liquid Line Size	Puron Charge oz/ft
3/8	0.60 (Factory charge for lineset = 9 oz)
5/16	0.40
1/4	0.27

Units are factory charged for 15 ft (4.6 m) of 3/8" liquid line. The factory charge for 3/8" lineset 9 oz. When using other length or diameter liquid lines, charge adjustments are required per the chart above.

### Charging Formula:

[(Lineset oz/ft x total length) – (factory charge for lineset)] = charge adjustment

**Example 1:** System has 15 ft of line set using existing 1/4" liquid line. What charge adjustment is required?

Formula: (.27 oz/ft x 15ft) – (9 oz) = (-4.95) oz.

Net result is to remove 4.95 oz of refrigerant from the system

**Example 2:** System has 45 ft of existing 5/16" liquid line. What is the charge adjustment?

Formula: (.40 oz/ft. x 45ft) – (9 oz.) = 9 oz.

Net result is to add 9 oz of refrigerant to the system

## LONG LINE APPLICATIONS

An application is considered Long Line, when the refrigerant level in the system requires the use of accessories to maintain acceptable refrigerant management for systems reliability. See Accessory Usage Guideline table for required accessories. Defining a system as long line depends on the liquid line diameter, actual length of the tubing, and vertical separation between the indoor and outdoor units.

For Air Conditioner systems, the charts below show when an application requires a TXV and long line accessories due to line set length.

### AC WITH PURON® REFRIGERANT LONG LINE DESCRIPTION ft (m) Beyond these lengths, TXV metering device is required

Liquid Line Size (in.)	Units On Same Level	Outdoor Below Indoor	Outdoor Above Indoor
1/4, 5/16, 3/8	50 (15.2)	20 (6.1)	20 (6.1)

**Note:** See Residential Piping and Long Line Guideline for details

### AC WITH PURON® REFRIGERANT LONG LINE DESCRIPTION ft (m) Beyond these lengths, long line accessories are required

Liquid Line Size	Units On Same Level	Outdoor Below Indoor	Outdoor Above Indoor
1/4	No accessories needed within allowed lengths	No accessories needed within allowed lengths	175 (53.3)
5/16	120 (36.6)	50 (15.2) vertical separation or 120 (36.6) total	120 (36.6)
3/8	80 (24.4)	35 (10.7) vertical separation or 80 (24.4) total	80 (24.4)

**Note:** See Residential Piping and Long Line Guideline for details

## VAPOR LINE SIZING AND COOLING CAPACITY LOSS

Acceptable vapor line diameters provide adequate oil return to the compressor while avoiding excessive capacity loss. The suction line diameters shown in the chart below are acceptable for AC systems with Puron refrigerant:

Unit Nominal Size (Btuh)	Maximum Liquid Line Diameters (In. OD)	Vapor Line Diameters (In. OD)	Cooling Capacity Loss (%) Total Equivalent Line Length ft. (m)								
			26–50 (7.9–15.2)	51–80 (15.5–24.4)	81–100 (24.7–30.5)	101–125 (30.8–38.1)	126–150 (38.4–45.7)	151–175 (46.0–53.3)	176–200 (53.6–61.0)	201–225 (61.3–68.6)	226–250 (68.9–76.2)
18000 1 Stage AC with Puron	3/8	1/2	1	2	3	5	6	7	8	9	11
		5/8	0	1	1	1	2	2	2	3	3
		3/4	0	0	0	0	1	1	1	1	1
24000 1 Stage AC with Puron	3/8	5/8	0	1	2	2	3	3	4	5	5
		3/4	0	0	1	1	1	1	1	2	2
		7/8	0	0	0	0	0	1	1	1	1
30000 1 Stage AC with Puron	3/8	5/8	1	2	3	3	4	5	6	7	8
		3/4	0	0	1	1	1	2	2	2	3
		7/8	0	0	0	0	1	1	1	1	1
36000 1 Stage AC with Puron	3/8	5/8	1	2	4	5	6	8	9	10	12
		3/4	0	1	1	2	2	3	3	4	4
		7/8	0	0	0	1	1	1	1	2	2
42000 1 Stage AC with Puron	3/8	3/4	0	1	2	2	3	4	4	5	6
		7/8	0	0	1	1	1	2	2	2	3
		1 1/8	0	0	0	0	0	0	0	0	0
48000 1 Stage AC with Puron	3/8	3/4	0	1	2	3	4	5	5	6	7
		7/8	0	0	1	1	2	2	2	3	3
		1 1/8	0	0	0	0	0	0	0	1	1
60000 1 Stage AC with Puron	3/8	3/4	1	2	4	5	6	7	9	10	11
		7/8	0	1	2	2	3	4	4	5	5
		1 1/8	0	0	0	1	1	1	1	1	1

Applications in this area may be long line and may have height restrictions. See the Residential Piping and Long Line Guideline.

## ACCESSORY THERMOSTATS

PART NUMBER	DESCRIPTION
T6-WEM01	Housewise™ Wi-Fi® thermostat
T6-PRH01-A	Programmable Relative Humidity Thermostat
T6-PAC01	Programmable Thermostat
T6-NRH01	Non-Programmable Relative Humidity Thermostat
T6-NAC01	Non-Programmable Thermostat
T2-WHS01	Wi-Fi® Thermostat
T2-PAC01	Programmable Thermostat
T2-NAC01	Non-Programmable Thermostat
T2SNAC01	Non-Programmable Standard Screen Thermostat

THERMOSTAT ACCESSORIES		
PART NUMBER	DESCRIPTION	THERMOSTATS USED WITH
T6-EXP	EXP® Card	T6-Pxx, T6-Nxx
TSTATXXSEN01-B	Outdoor Air Temperature Sensor	T6-Pxx, T6-Nxx
TSTATXXCNV10	Thermostat Conversion Kit (4 to 5 wire) - 10 pack	All Bryant® branded thermostats
TX-MBP01	Medium Decorative Backplate	T2-Nxx
TX-LBP01	Large Decorative Backplate	T6-Pxx, T6-Nxx, T2-Pxx

## ACCESSORIES

Accessory Kit Number	Description	18	24	30	36	42	48	60
HC32GR237	BALL BEARING FAN MOTOR	X						
HB32GR229	BALL BEARING FAN MOTOR		X					
HC34GE240	BALL BEARING FAN MOTOR			X	X			
HC40GE226	BALL BEARING FAN MOTOR					X	X	
HC40GE228	BALL BEARING FAN MOTOR							X
KAACH1201AAA	CRKC HTR KIT					X	X	
KAACH1401AAA	CRKC HTR KIT	X		X	X			
KAACH1601AAA	CRKC HTR KIT							S
KAACH1701AAA	CRKC HTR KIT		X					
KAACS0201PTC	KIT PTC	X	X	X	X	X	X	X
KAHI0501PUR	HIGH PRESSURE SW KIT	X	X	X	X	X	X	X
KAALP0401PUR	LOW PRESSURE SW KIT	X	X	X	X	X	X	X
KAALS0201LLS	SOLENOID VALVE KIT	X	X	X	X	X	X	X
KAATD0101TDR	TIME DELAY KIT	X	X	X	X	X	X	X
KAAWS0101AAA	WINTER START KIT	X	X	X	X	X	X	X
KSACY0101AAA	CYCLE PROTR KIT	X	X	X	X	X	X	X
KSFT0101AAA	FRZ THERM KIT	X	X	X	X	X	X	X
KSAS1701AAA	HARD START KIT	X	X	X	X	X	X	X
KSALA0301410	LOW AMBIENT KIT	X	X	X	X	X	X	X
KSALA0601AAA	MOTORMASTER KIT	X	X	X	X	X	X	X
KSASF0101AAA	SUPPORT FEET		X	X	X	X	X	X
KSASF0201AAA	SUPPORT FEET	X						
KSASH0601COP	SOUND BLKT	X	X	X	X		X	
KSASH2101COP	SOUND BLKT					X		X
KSATX0201PUR	TXV PURON (R-410A), COPPER/TIN COILS OINLY	X	X	X				
KSATX0301PUR	TXV PURON (R-410A), COPPER/TIN COILS OINLY				X	X		
KSATX0401PUR	TXV PURON (R-410A), COPPER/TIN COILS OINLY						X	
KSATX0501PUR	TXV PURON (R-410A), COPPER/TIN COILS OINLY							X
KSBTX0201PUR	TXV PURON (R-410A), ALUMINUM COILS OINLY	X	X	X				
KSBTX0301PUR	TXV PURON (R-410A), ALUMINUM COILS OINLY				X	X		
KSBTX0401PUR	TXV PURON (R-410A), ALUMINUM COILS OINLY						X	
KSBTX0501PUR	TXV PURON (R-410A), ALUMINUM COILS OINLY							X

X = Accessory S = Standard

# ACCESSORY USAGE GUIDELINE

ACCESSORY	REQUIRED FOR LOW-AMBI-ENT COOLING APPLICATIONS (Below 55°F/12.8°C)	REQUIRED FOR LONG LINE APPLICATIONS*	REQUIRED FOR SEA COAST APPLICATIONS (Within 2 miles/3.22 km)
Ball Bearing Fan Motor	Yes†	No	No
Compressor Start Assist Capacitor and Relay	Yes	Yes	No
Crankcase Heater	Yes	Yes	No
Evaporator Freeze Thermostat	Yes	No	No
Hard Shut-Off TXV	Yes	Yes‡	No
Liquid Line Solenoid Valve	No	No	No
Motor Master® Control or Low-ambient Pressure Switch	Yes	No	No
Support Feet	Recommended	No	Recommended
Winter Start Control	Yes	No	No

\* For tubing line sets between 50 and 200 ft. (15.2 and 61.0 m) and/or 20 ft. (6.1 m) vertical differential, refer to Residential Piping and Longline Guideline.

† Required for Low-Ambient Controller (full modulation feature) MotorMaster® Control.

‡ TXV required beyond 20 ft (6.1m) vertical separation or 50 ft (15.2 m) total length.

## Accessory Description and Usage (Listed Alphabetically)

### 1. Ball-Bearing Fan Motor

A fan motor with ball bearings which permits speed reduction while maintaining bearing lubrication.

Usage Guideline:

Required on all units when MotorMaster® is used.

### 2. Compressor Start Assist - Capacitor and Relay

Start capacitor and relay gives a "hard" boost to compressor motor at each start up.

Usage Guideline:

Required for reciprocating compressors in the following applications:

Long line

Low ambient cooling

Hard shut off expansion valve on indoor coil

Liquid line solenoid on indoor coil

Required for single-phase scroll compressors in the following applications:

Long line

Low ambient cooling

Suggested for all compressors in areas with a history of low voltage problems.

### 3. Compressor Start Assist — PTC Type

Solid state electrical device which gives a "soft" boost to the compressor at each start-up.

Usage Guideline:

Suggested in installations with marginal power supply.

### 4. Crankcase Heater

An electric resistance heater which mounts to the base of the compressor to keep the lubricant warm during off cycles. Improves compressor lubrication on restart and minimizes the chance of liquid slugging.

Usage Guideline:

Required in low ambient cooling applications.

Required in long line applications.

Suggested in all commercial applications.

### 5. Cycle Protector

The cycle protector is designed to prevent compressor short cycling. This control provides an approximate 5-minute delay after power to the compressor has been interrupted for any reason, including power outage, protector control trip, thermostat jiggling, or normal cycling.

### 6. Evaporator Freeze Thermostat

An SPST temperature-actuated switch that stops unit operation when evaporator reaches freeze-up conditions.

Usage Guideline:

Required when low ambient kit has been added.

### 7. Low-Ambient Pressure Switch Kit

A long life pressure switch which is mounted to outdoor unit service valve. It is designed to cycle the outdoor fan motor in order to maintain head pressure within normal operating limits (approximately 100 psig to 225 psig). The control will maintain working head pressure at low-ambient temperatures down to 0°F (-18°C) when properly installed.

Usage Guideline:

A Low-Ambient Pressure Switch or MotorMaster® Low-Ambient Controller must be used when cooling operation is used at outdoor temperatures below 55°F (12.8°C).

### 8. MotorMaster® Low-Ambient Controller

A fan-speed control device activated by a temperature sensor, designed to control condenser fan motor speed in response to the saturated, condensing temperature during operation in cooling mode only. For outdoor temperatures down to -20°F (-28.9°C), it maintains condensing temperature at 100°F ±10°F (37.8°C ± 5.5°C).

Usage Guideline:

A MotorMaster® Low Ambient Controller or Low-Ambient Pressure Switch must be used when cooling operation is used at outdoor temperatures below 55°F (12.8°C).

Suggested for all commercial applications.

### 9. Outdoor Air Temperature Sensor

Designed for use with Bryant Thermostats listed in this publication. This device enables the thermostat to display the outdoor temperature. This device also is required to enable special thermostat features such as auxiliary heat lock out.

Usage Guideline:

Suggested for all Bryant thermostats listed in this publication.

## Accessory Description and Usage (Listed Alphabetically) (Continued)

### 10. Support Feet

Four stick-on plastic feet that raise the unit 4 in. (101.6 mm) above the mounting pad. This allows sand, dirt, and other debris to be flushed from the unit base, minimizing corrosion.

Usage Guideline:

Suggested in the following applications:

Coastal installations.

Windy areas or where debris is normally circulating.

Rooftop installations.

For improved sound ratings.

### 11. Thermostatic Expansion Valve (TXV)

A modulating flow-control valve which meters refrigerant liquid flow rate into the evaporator in response to the superheat of the refrigerant gas leaving the evaporator.

Kit includes valve, adapter tubes, and external equalizer tube. Hard shut off types are available.

**NOTE:** When using a hard shut off TXV with single phase reciprocating compressors, a Compressor Start Assist Capacitor and Relay is required.

Usage Guideline:

Required to achieve AHRI ratings in certain equipment combinations. Refer to combination ratings.

Hard shut off TXV or LLS required in air conditioner applications beyond 50ft (15.2m) total length or when indoor and outdoor units have over 20ft (6.1m) vertical separation.

Required for use on all zoning systems.

### 12. Time-Delay Relay

An SPST delay relay which briefly continues operation of indoor blower motor to provide additional cooling after the compressor cycles off.

**NOTE:** Most indoor unit controls include this feature. For those that do not, use the guideline below.

Usage Guideline:

For improved efficiency ratings for certain combinations of indoor and outdoor units. Refer to AHRI Unitary Directory.

### 13. Winter Start Control

This control is designed to alleviate nuisance opening of the low-pressure switch by bypassing it for the first 3 minutes of operation.

## ELECTRICAL DATA

UNIT SIZE - SERIES	V/PH	OPER VOLTS*		COMPR		FAN	MCA	MAX FUSE† or CKT BRK AMPS
		MAX	MIN	LRA	RLA	FLA		
18-A	208/230/1-60	253	197	47.5	9.0	0.40	11.7	20
24-A				62.9	10.9	0.50	14.1	25
30-A				67.8	12.8	0.75	16.8	25
36-A				78.0	13.6	0.75	17.8	30
42-A				109.0	16.7	1.40	22.3	35
48-A				124.0	18.5	1.40	24.5	40
60-A				144.2	24.4	1.20	31.7	50

\* Permissible limits of the voltage range at which the unit will operate satisfactorily

† Time-Delay fuse.

FLA - Full Load Amps

LRA - Locked Rotor Amps

MCA - Minimum Circuit Amps

RLA - Rated Load Amps

NOTE: Control circuit is 24V on all units and requires external power source. Copper wire must be used from service disconnect to unit.  
All motors/compressors contain internal overload protection.

Complies with 2010 requirements of ASHRAE Standards 90.1

## A-WEIGHTED SOUND POWER (dBA)

UNIT SIZE - SERIES	Standard Rating (dBA)	TYPICAL OCTAVE BAND SPECTRUM (dBA without tone adjustment)						
		125	250	500	1000	2000	4000	8000
18-A	76	50.3	58.1	63.6	73.5	69.3	65.1	54.0
24-A	73	53.2	61.6	65.2	69.8	65.0	61.4	53.8
30-A	76	57.0	64.5	70.3	72.5	68.4	64.1	57.8
36-A	77	53.8	64.4	69.9	73.5	69.5	66.2	59.7
42-A	76	58.7	68.0	69.7	70.1	67.6	64.5	57.1
48-A	75	52.7	67.4	62.5	69.2	62.4	57.6	49.7
60-A	73	52.2	56.7	60.9	66.1	59.2	57.4	50.9

NOTE: Tested in compliance with AHRI 270-1995 (not listed with AHRI)

## A-WEIGHTED SOUND POWER (dBA) WITH SOUND SHIELD

UNIT SIZE - SERIES	Standard Rating (dBA)	TYPICAL OCTAVE BAND SPECTRUM (dBA without tone adjustment)						
		125	250	500	1000	2000	4000	8000
18-A	72	51.0	57.7	63.1	69.7	64.7	59.5	53.2
24-A	72	54.4	62.0	65.0	67.7	64.1	60.8	53.1
30-A	76	56.2	64.7	69.9	71.7	68.2	63.8	57.1
36-A	76	53.7	64.5	69.5	72.3	68.5	65.2	59.3
42-A	75	58.9	67.0	69.4	69.7	66.7	61.9	53.5
48-A	74	52.3	66.2	62.3	68.2	62.4	56.3	47.9
60-A	72	51.3	56.9	60.1	64.5	59.2	54.8	48.1

NOTE: Tested in compliance with AHRI 270-1995 (not listed with AHRI)

## METERING DEVICE

UNIT SIZE - SERIES	REQUIRED SUBCOOLING °F (°C)
18-A	11 (6.11)
24-A	11 (6.11)
30-A	8 (4.44)
36-A	8 (4.44)
42-A	10 (5.56)
48-A	11 (6.11)
60-A	15 (8.33)






# DIMENSIONS - SI


UNIT	SERIES	ELECTRICAL CHARACTERISTICS	A	B	C	D	E	F	G	K	L	M	N	P	OPERATING WEIGHT (Kgs)	SHIPPING WEIGHT (Kgs)	SHIPPING DIMENSIONS (L x W x H)
114CNC018	A	X 0 0 0	587.4	722.3	95.2	19.0	112.7	458.8	198.4	71.4	12.7	304.8	317.5	349.3	50.3	60.3	612.8 X 612.8 X 777.9
114CNC024	A	X 0 0 0	792.2	722.3	95.2	19.0	166.7	627.7	231.8	71.4	12.7	381.0	406.4	362.0	61.7	77.1	846.6 X 846.6 X 777.9
114CNC030	A	X 0 0 0	792.2	630.2	95.2	19.0	166.7	627.7	231.8	71.4	12.7	406.4	419.1	311.2	68.7	83.0	846.6 X 846.6 X 690.6
114CNC036	A	X 0 0 0	792.2	630.2	98.4	22.2	166.7	627.7	231.8	74.6	15.9	431.8	381.0	304.8	70.3	84.4	846.6 X 846.6 X 690.6
114CNC042	A	X 0 0 0	792.2	722.3	98.4	22.2	166.7	627.7	231.8	74.6	15.9	400.1	438.2	368.3	85.7	99.8	846.6 X 846.6 X 777.9
114CNC048	A	X 0 0 0	792.2	908.0	98.4	22.2	166.7	627.7	231.8	74.6	15.9	422.3	387.4	412.8	90.3	105.7	846.6 X 846.6 X 1016.9
114CNC060	A	X 0 0 0	889.0	993.8	98.4	22.2	166.7	722.3	231.8	74.6	15.9	406.4	450.9	495.3	112.5	131.1	917.6 X 917.6 X 1085.8

X = YES  
O = NO

208-230-160	230-160	208/230-3-60	460-3-60
-------------	---------	--------------	----------

### NOTES:


- ALLOW 762.0 CLEARANCE TO SERVICE SIDE OF UNIT, 1219.2 ABOVE UNIT, 1152.4 ON ONE SIDE, 304.8 ON REMAINING SIDE, AND 609.6 BETWEEN UNITS FOR PROPER AIRFLOW.
- MINIMUM OUTDOOR OPERATING AMBIENT IN COOLING MODE IS 13 C, MAX. 52 C.
- SERIES DESIGNATION IS THE 14TH POSITION OF THE UNIT MODEL NUMBER.
- CENTER OF GRAVITY 
- ALL DIMENSIONS ARE IN "MM" UNLESS NOTED.



UNIT SIZE	"X" MIN GROUND MOUNTING PAD APPLICATION DIMENSIONS	"Y" MIN ROOF-TOP MOUNTING PAD APPLICATION DIMENSIONS
18	587.3	451.3
-	654.0	518.5
24 THRU 48	792.2	583.2
60	889.0	679.7

# CLEARANCES

Clearances (various examples)



**Note: Numbers in ( ) = mm**

**IMPORTANT:** When installing multiple units in an alcove, roof well, or partially enclosed area, ensure there is adequate ventilation to prevent re-circulation of discharge air.

## TESTED AHRI COMBINATION RATINGS

**NOTE:** Ratings contained in this document are subject to change at any time.

For AHRI ratings certificates, please refer to the AHRI directory [www.ahridirectory.org](http://www.ahridirectory.org)

Additional ratings and system combinations can be accessed via the Bryant database at: [www.MyBryantRatings.com](http://www.MyBryantRatings.com)

For performance data at specific application &/or design conditions with various indoor unit combinations, the equipment performance calculator can be accessed at : <http://rpmobbry.wrightsoft.com/>

114CNC UNIT SIZE – SERIES	INDOOR MODEL	AHRI STANDARD RATINGS						FURNACE MODEL
		COOLING						
		CAPACITY	FACTORY ENHANCE	SEER			EER	
STANDARD	TDR			TXV				
018–A	*CAP**1917AL*	17,500	TXV		14.00		11.70	
024–A	*CAP**2517AL*	23,400	TXV		14.00		11.70	
030–A	*CAP**3721AL*	29,600	TXV		14.50		12.00	
036–A	*CAP**3721AL*	34,200	TXV		14.00		12.00	
042–A	*CAP**4321AL*	38,500	TXV		14.00		12.00	
048–A	*CAP**6124AL*	45,000	TXV		14.50		11.70	
060–A	*CAP**6024AL*	56,500	TXV		14.00		11.70	

**AHRI** — Air Conditioning, Heating & Refrigeration Institute

**EER** — Energy Efficiency Ratio – 80°F (26.6°C) indoor db/67°F (19.4°C) indoor wb & 95°F (35°C) outdoor wb.

**SEER** — Seasonal Energy Efficiency Ratio

**TDR** — Time–Delay Relay. In most cases, only one method should be used to achieve TDR function. Using more than one method in a system may cause degradation in performance.

Use either the accessory Time–Delay Relay, KAATD0101TDR, or a furnace equipped with TDR. Most Bryant furnaces are equipped with TDR.

**NOTES:**

1. Ratings are net values reflecting the effects of circulating fan motor heat. Supplemental electric heat is not included.
2. Tested outdoor/indoor combinations have been tested in accordance with DOE test procedures for central air conditioners. Ratings for other combinations are determined under DOE computer simulation procedures.
3. Determine actual CFM values obtainable for your system by referring to fan performance data in fan coil or furnace coil literature.
4. Do not apply with capillary tube coils as performance and reliability are significantly affected.

# DETAILED COOLING CAPACITIES#

EVAPORATOR AIR		CONDENSER ENTERING AIR TEMPERATURES ° F (° C)																	
		75 (23.9)			85 (29.4)			95 (35)			105 (40.6)			115 (46.1)			125 (51.7)		
		CFM	EWB ° F (° C)	Capacity MBtuh		Total System KW**	Capacity MBtuh		Total System KW**	Capacity MBtuh		Total System KW**	Capacity MBtuh		Total System KW**	Capacity MBtuh		Total System KW**	
Total	Sens†			Total	Sens†		Total	Sens†		Total	Sens†		Total	Sens†		Total	Sens†		
<b>114CNC018-A Outdoor Section With CAP**1917AL* Indoor Section</b>																			
<b>525</b>	57 (13.9)	16.93	16.93	1.22	16.34	16.34	1.36	15.71	15.71	1.52	15.01	15.01	1.70	14.22	14.22	1.90	13.32	13.32	2.14
	62 (16.7)	17.34	15.33	1.22	16.61	15.01	1.36	15.83	14.65	1.52	15.04	15.04	1.70	14.24	14.24	1.90	13.35	13.35	2.14
	63 (17.2)††	17.70	12.46	1.22	16.95	12.14	1.36	16.14	11.81	1.52	15.26	11.44	1.70	14.23	11.03	1.91	13.10	10.58	2.14
	67 (19.4)	18.99	12.91	1.21	18.22	12.62	1.35	17.40	12.30	1.51	16.49	11.95	1.69	15.45	11.57	1.90	14.25	11.12	2.14
	72 (22.2)	20.79	10.44	1.20	20.01	10.16	1.34	19.16	9.87	1.54	18.22	9.54	1.69	17.14	9.18	1.90	15.88	8.75	2.14
<b>600</b>	57 (13.9)	17.65	17.65	1.25	17.03	17.03	1.39	16.37	16.37	1.54	15.64	15.64	1.72	14.81	14.81	1.93	13.86	13.86	2.17
	62 (16.7)	17.72	17.63	1.25	17.06	17.06	1.39	16.40	16.40	1.54	15.67	15.67	1.72	14.83	14.83	1.93	13.88	13.88	2.17
	63 (17.2)††	18.03	13.32	1.25	17.25	13.01	1.39	16.43	12.67	1.55	15.51	12.30	1.73	14.47	11.88	1.94	13.30	11.42	2.17
	67 (19.4)	19.31	13.84	1.24	18.53	13.54	1.38	17.68	13.23	1.54	16.74	12.88	1.72	15.68	12.48	1.93	14.46	12.03	2.17
	72 (22.2)	21.14	11.01	1.23	20.33	10.74	1.37	19.46	10.44	1.54	18.49	10.12	1.72	17.38	9.75	1.93	16.08	9.32	2.17
<b>675</b>	57 (13.9)	18.25	18.25	1.27	17.61	17.61	1.41	16.92	16.92	1.57	16.16	16.16	1.75	15.30	15.30	1.96	14.30	14.30	2.20
	62 (16.7)	18.27	18.27	1.27	17.63	17.63	1.41	16.95	16.95	1.57	16.18	16.18	1.75	15.32	15.32	1.96	14.32	14.32	2.20
	63 (17.2)††	18.27	14.16	1.27	17.48	13.84	1.42	16.63	13.50	1.57	15.71	13.13	1.76	14.64	12.71	1.96	13.46	12.22	2.20
	67 (19.4)	19.55	14.75	1.26	18.75	14.45	1.41	17.89	14.13	1.57	16.93	13.78	1.75	15.86	13.38	1.96	14.61	12.92	2.20
	72 (22.2)	21.38	11.58	1.25	20.56	11.30	1.40	19.67	11.01	1.56	18.67	10.68	1.75	17.54	10.31	1.96	16.21	9.88	2.20

EVAPORATOR AIR		CONDENSER ENTERING AIR TEMPERATURES ° F (° C)																	
		75 (23.9)			85 (29.4)			95 (35)			105 (40.6)			115 (46.1)			125 (51.7)		
		CFM	EWB ° F (° C)	Capacity MBtuh		Total System KW**	Capacity MBtuh		Total System KW**	Capacity MBtuh		Total System KW**	Capacity MBtuh		Total System KW**	Capacity MBtuh		Total System KW**	
Total	Sens†			Total	Sens†		Total	Sens†		Total	Sens†		Total	Sens†		Total	Sens†		
<b>114CNC024-A Outdoor Section With CAP**2517AL* Indoor Section</b>																			
<b>700</b>	57 (13.9)	22.60	22.60	1.58	21.79	21.79	1.74	20.95	20.95	1.93	20.03	20.03	2.15	19.04	19.04	2.40	17.93	17.93	2.70
	62 (16.7)	23.23	20.43	1.58	22.21	19.98	1.74	21.14	19.51	1.93	20.06	20.06	2.15	19.07	19.07	2.40	17.96	17.96	2.70
	63 (17.2)††	23.72	16.63	1.58	22.67	16.19	1.74	21.57	15.73	1.93	20.40	15.25	2.15	19.14	14.73	2.40	17.75	14.18	2.70
	67 (19.4)	25.49	17.26	1.58	24.38	16.83	1.74	23.21	16.37	1.93	21.97	15.89	2.15	20.63	15.39	2.40	19.14	14.84	2.69
	72 (22.2)	27.98	14.00	1.57	26.78	13.57	1.74	25.51	13.13	1.93	24.16	12.66	2.15	22.70	12.17	2.40	21.11	11.63	2.69
<b>800</b>	57 (13.9)	23.60	23.60	1.61	22.74	22.74	1.78	21.83	21.83	1.97	20.84	20.84	2.19	19.78	19.78	2.44	18.59	18.59	2.73
	62 (16.7)	23.75	22.07	1.61	22.77	22.77	1.78	21.86	21.86	1.97	20.88	20.88	2.19	19.81	19.81	2.44	18.62	18.62	2.73
	63 (17.2)††	24.18	17.77	1.61	23.09	17.33	1.78	21.94	16.86	1.97	20.73	16.37	2.19	19.42	15.85	2.44	17.99	15.28	2.74
	67 (19.4)	25.97	18.49	1.61	24.81	18.05	1.78	23.59	17.59	1.97	22.29	17.10	2.19	20.90	16.59	2.44	19.38	16.03	2.73
	72 (22.2)	28.48	14.77	1.61	27.23	14.34	1.78	25.90	13.89	1.97	24.49	13.42	2.18	22.98	12.91	2.44	21.34	12.37	2.72
<b>900</b>	57 (13.9)	24.44	24.44	1.65	23.52	23.52	1.82	22.55	22.55	2.01	21.51	21.51	2.22	20.39	20.39	2.48	19.13	19.13	2.77
	62 (16.7)	24.48	24.48	1.65	23.55	23.55	1.82	22.59	22.59	2.01	21.54	21.54	2.22	20.42	20.42	2.48	19.15	19.15	2.77
	63 (17.2)††	24.53	18.89	1.65	23.39	18.43	1.82	22.21	17.96	2.01	20.97	17.46	2.23	19.63	16.93	2.48	18.16	16.33	2.77
	67 (19.4)	26.32	19.69	1.65	25.12	19.24	1.82	23.86	18.77	2.01	22.53	18.28	2.22	21.11	17.76	2.48	19.55	17.18	2.77
	72 (22.2)	28.83	15.52	1.65	27.54	15.09	1.82	26.17	14.63	2.01	24.72	14.16	2.22	23.17	13.65	2.47	21.48	13.10	2.76

See notes on page 16

# DETAILED COOLING CAPACITIES# CONTINUED

EVAPORATOR AIR		CONDENSER ENTERING AIR TEMPERATURES ° F (° C)																	
		75 (23.9)			85 (29.4)			95 (35)			105 (40.6)			115 (46.1)			125 (51.7)		
CFM	EWB ° F (° C)	Capacity MBtuh		Total System KW**	Capacity MBtuh		Total System KW**	Capacity MBtuh		Total System KW**	Capacity MBtuh		Total System KW**	Capacity MBtuh		Total System KW**			
		Total	Sens†		Total	Sens†		Total	Sens†		Total	Sens†		Total	Sens†		Total	Sens†	
<b>114CNC036-A Outdoor Section With CAP**3721AL * Indoor Section</b>																			
<b>875</b>	57 (13.9)	28.18	28.18	1.89	27.13	27.13	2.08	26.02	26.02	2.29	24.83	24.83	2.53	23.54	23.54	2.81	22.12	22.12	3.14
	62 (16.7)	28.80	26.55	1.89	27.49	25.95	2.08	26.13	26.00	2.29	24.87	24.87	2.53	23.57	23.57	2.81	22.15	22.15	3.14
	63 (17.2)††	29.39	21.55	1.89	28.03	20.96	2.08	26.60	20.35	2.29	25.10	19.71	2.53	23.49	19.04	2.81	21.75	18.32	3.14
	67 (19.4)	31.59	22.38	1.89	30.13	21.79	2.08	28.60	21.19	2.29	26.98	20.55	2.53	25.25	19.88	2.81	23.39	19.16	3.14
	72 (22.2)	34.68	18.09	1.89	33.08	17.51	2.07	31.40	16.91	2.29	29.63	16.28	2.53	27.73	15.92	2.81	25.70	14.92	3.14
<b>1000</b>	57 (13.9)	29.40	29.40	1.94	28.27	27.07	2.13	27.07	27.07	2.34	25.79	25.79	2.58	24.40	24.40	2.86	22.88	22.88	3.19
	62 (16.7)	29.47	29.43	1.94	28.31	28.31	2.13	27.11	27.11	2.34	25.83	25.83	2.58	24.43	24.43	2.86	22.91	22.91	3.19
	63 (17.2)††	29.93	23.04	1.94	28.52	22.44	2.13	27.03	21.82	2.34	25.46	21.16	2.58	23.80	20.48	2.86	22.00	19.74	3.19
	67 (19.4)	32.15	23.99	1.94	30.62	23.39	2.12	29.03	22.77	2.33	27.95	22.12	2.58	25.55	21.43	2.86	23.64	20.70	3.19
	72 (22.2)	35.25	19.10	1.94	33.59	18.52	2.12	31.84	17.90	2.33	29.99	17.26	2.58	28.03	16.80	2.86	25.93	15.89	3.19
<b>1125</b>	57 (13.9)	30.42	30.42	1.99	29.21	29.21	2.17	27.93	27.93	2.38	26.57	26.57	2.62	25.10	25.10	2.91	23.50	23.50	3.24
	62 (16.7)	30.46	30.46	1.99	29.25	29.25	2.17	27.97	27.97	2.38	26.61	26.61	2.62	25.13	25.13	2.91	23.52	23.52	3.24
	63 (17.2)††	30.34	24.49	1.99	28.87	23.88	2.17	27.34	23.24	2.38	25.73	22.58	2.63	24.02	21.87	2.91	22.20	21.08	3.24
	67 (19.4)	32.56	25.55	1.98	30.99	24.94	2.17	28.34	24.31	2.38	27.61	23.64	2.62	25.78	22.94	2.91	23.83	22.17	3.24
	72 (22.2)	35.66	20.09	1.98	33.94	19.49	2.17	32.13	18.87	2.38	30.24	18.23	2.62	28.22	17.55	2.91	26.07	16.83	3.24
<b>CONDENSER ENTERING AIR TEMPERATURES ° F (° C)</b>																			
EVAPORATOR AIR		CONDENSER ENTERING AIR TEMPERATURES ° F (° C)																	
		75 (23.9)			85 (29.4)			95 (35)			105 (40.6)			115 (46.1)			125 (51.7)		
CFM	EWB ° F (° C)	Capacity MBtuh		Total System KW**	Capacity MBtuh		Total System KW**	Capacity MBtuh		Total System KW**	Capacity MBtuh		Total System KW**	Capacity MBtuh		Total System KW**			
		Total	Sens†		Total	Sens†		Total	Sens†		Total	Sens†		Total	Sens†		Total	Sens†	
<b>114CNC036-A Outdoor Section With CAP**3721AL * Indoor Section</b>																			
<b>1050</b>	57 (13.9)	33.25	33.25	2.27	32.03	32.03	2.52	30.75	30.75	2.78	29.33	29.33	3.07	27.70	27.70	3.43	25.82	25.82	3.86
	62 (16.7)	33.81	31.48	2.27	32.31	30.77	2.52	30.80	30.80	2.78	29.38	29.38	3.07	27.74	27.74	3.43	25.85	25.85	3.86
	63 (17.2)††	34.45	25.48	2.27	32.89	24.81	2.52	31.26	24.12	2.78	29.49	23.37	3.07	27.48	22.53	3.42	25.20	21.59	3.85
	67 (19.4)	37.03	26.49	2.28	35.36	25.82	2.53	33.60	25.12	2.80	31.67	24.37	3.10	29.52	23.53	3.45	27.07	22.60	3.88
	72 (22.2)	40.65	21.36	2.29	38.82	20.70	2.56	36.88	20.01	2.83	34.76	19.26	3.14	32.38	18.44	3.50	29.72	17.53	3.94
<b>1200</b>	57 (13.9)	34.65	34.65	2.33	33.34	33.34	2.58	31.96	31.96	2.85	30.43	30.43	3.14	28.67	28.67	3.50	26.66	26.66	3.94
	62 (16.7)	34.70	34.70	2.33	33.39	33.39	2.59	32.00	32.00	2.85	30.47	30.47	3.15	28.71	28.71	3.50	26.70	26.70	3.94
	63 (17.2)††	35.06	27.25	2.33	33.44	26.57	2.59	31.74	25.86	2.85	29.89	25.09	3.14	27.82	24.23	3.49	25.48	23.26	3.92
	67 (19.4)	37.65	28.39	2.34	35.91	27.70	2.60	34.08	26.99	2.86	32.08	26.22	3.16	29.85	25.37	3.52	27.35	24.41	3.95
	72 (22.2)	41.28	22.56	2.36	39.39	21.89	2.63	37.36	21.18	2.90	35.16	20.42	3.21	32.70	19.59	3.57	29.96	18.66	4.01
<b>1350</b>	57 (13.9)	35.82	35.82	2.39	34.43	34.43	2.65	32.95	32.95	2.92	31.32	31.32	3.22	29.46	29.46	3.57	27.34	27.34	4.01
	62 (16.7)	35.87	35.87	2.39	34.47	34.47	2.65	32.99	32.99	2.92	31.36	31.36	3.22	29.50	29.50	3.57	27.37	27.37	4.01
	63 (17.2)††	35.52	28.96	2.39	33.84	28.26	2.65	32.09	27.54	2.91	30.20	26.75	3.20	28.08	25.86	3.55	25.73	25.53	3.98
	67 (19.4)	38.11	30.23	2.40	36.32	29.54	2.66	34.43	28.81	2.93	32.38	28.02	3.23	30.10	27.14	3.58	27.57	26.11	4.02
	72 (22.2)	41.74	23.70	2.42	39.77	23.03	2.69	37.69	22.31	2.97	35.42	21.54	3.28	32.90	20.70	3.64	30.09	19.76	4.08

See notes on page 16

# DETAILED COOLING CAPACITIES# CONTINUED

EVAPORATOR AIR		CONDENSER ENTERING AIR TEMPERATURES ° F (° C)																	
		75 (23.9)			85 (29.4)			95 (35)			105 (40.6)			115 (46.1)			125 (51.7)		
		CFM	EWB ° F (° C)	Capacity MBtuh		Total System KW**	Capacity MBtuh		Total System KW**	Capacity MBtuh		Total System KW**	Capacity MBtuh		Total System KW**	Capacity MBtuh		Total System KW**	
Total	Sens†			Total	Sens†		Total	Sens†		Total	Sens†		Total	Sens†		Total	Sens†		
<b>114CNC042-A Outdoor Section With CAP**4321AL * Indoor Section</b>																			
1250	57 (13.9)	39.42	38.01	3.03	36.54	36.54	3.32	34.94	34.94	3.67	33.18	33.18	4.07	31.18	31.18	4.54			
	62 (16.7)	40.19	36.52	2.77	36.68	36.45	3.32	35.00	35.00	3.67	33.23	33.23	4.07	31.23	31.23	4.54			
	63 (17.2)††	40.88	29.60	2.77	39.07	28.82	3.03	37.20	27.20	3.67	33.02	26.30	4.07	30.60	25.31	4.54			
	67 (19.4)	43.99	30.77	2.78	42.03	29.99	3.04	40.00	29.20	3.33	37.84	28.36	3.68	35.49	27.46	4.08	26.48		
	72 (22.2)	48.32	24.89	2.80	46.14	24.11	3.05	43.88	23.31	3.34	41.51	22.48	3.69	38.93	21.60	4.09	20.83		
1400	57 (13.9)	40.85	40.85	2.83	39.34	39.34	3.09	37.77	37.77	3.38	36.07	36.07	3.73	34.19	34.19	4.13			
	62 (16.7)	41.02	40.70	2.83	39.40	37.83	3.39	37.83	37.83	3.39	36.12	36.12	3.73	34.24	34.24	4.13			
	63 (17.2)††	41.52	31.30	2.83	39.63	30.50	3.09	37.69	29.70	3.38	35.64	28.85	3.73	33.38	27.93	4.13			
	67 (19.4)	44.65	32.60	2.84	42.60	31.80	3.10	40.50	30.99	3.39	38.28	30.14	3.74	35.86	29.22	4.14			
	72 (22.2)	48.99	26.03	2.86	46.72	25.23	3.11	44.39	24.43	3.40	41.94	23.59	3.75	39.27	22.69	4.15			
1575	57 (13.9)	42.20	42.20	2.91	40.58	40.58	3.17	38.91	38.91	3.46	37.10	37.10	3.81	35.11	35.11	4.21			
	62 (16.7)	42.26	42.26	2.91	40.64	40.64	3.17	38.96	38.96	3.46	37.15	37.15	3.81	35.16	35.16	4.21			
	63 (17.2)††	42.05	33.19	2.91	40.11	32.38	3.17	38.11	31.56	3.46	35.98	30.69	3.81	33.69	29.74	4.21			
	67 (19.4)	45.19	34.65	2.92	43.08	33.83	3.18	40.92	33.01	3.47	38.62	32.13	3.81	36.15	31.18	4.22			
	72 (22.2)	49.54	27.30	2.94	47.20	26.50	3.19	44.79	25.68	3.48	42.25	24.82	3.82	39.53	23.92	4.22			
<b>CONDENSER ENTERING AIR TEMPERATURES ° F (° C)</b>																			
EVAPORATOR AIR		CONDENSER ENTERING AIR TEMPERATURES ° F (° C)																	
		75 (23.9)			85 (29.4)			95 (35)			105 (40.6)			115 (46.1)			125 (51.7)		
		CFM	EWB ° F (° C)	Capacity MBtuh		Total System KW**	Capacity MBtuh		Total System KW**	Capacity MBtuh		Total System KW**	Capacity MBtuh		Total System KW**	Capacity MBtuh		Total System KW**	
Total	Sens†			Total	Sens†		Total	Sens†		Total	Sens†		Total	Sens†		Total	Sens†		
<b>114CNC048-A Outdoor Section With CAP**6024AL * Indoor Section</b>																			
1400	57 (13.9)	44.69	44.69	3.13	43.10	43.10	3.43	41.40	41.40	3.77	39.55	39.55	4.17	37.50	37.50	4.62			
	62 (16.7)	45.72	42.76	3.14	43.76	41.81	3.43	41.71	40.78	3.78	39.60	39.60	4.17	37.55	37.55	4.62			
	63 (17.2)††	46.45	34.73	3.14	44.39	33.80	3.43	42.24	32.85	3.78	39.91	31.83	4.17	37.37	30.72	4.62			
	67 (19.4)	50.04	36.11	3.14	47.83	35.19	3.44	45.50	34.22	3.79	42.99	33.20	4.19	40.28	32.10	4.64			
	72 (22.2)	55.01	29.34	3.15	52.60	28.43	3.46	50.04	27.47	3.81	47.28	26.45	4.21	44.28	25.36	4.67			
1600	57 (13.9)	46.53	46.53	3.21	44.82	44.82	3.51	42.99	42.99	3.86	41.00	41.00	4.26	38.81	38.81	4.71			
	62 (16.7)	46.81	45.90	3.21	44.86	44.86	3.51	43.05	43.05	3.86	41.06	41.06	4.26	38.86	38.86	4.71			
	63 (17.2)††	47.29	36.94	3.22	45.17	36.01	3.51	42.91	35.03	3.86	40.50	33.98	4.26	37.88	32.85	4.70			
	67 (19.4)	50.90	38.48	3.22	48.62	37.56	3.52	46.20	36.58	3.87	43.58	35.53	4.27	40.78	34.40	4.72			
	72 (22.2)	55.94	30.83	3.23	53.43	29.90	3.54	50.75	28.92	3.89	47.88	27.88	4.29	44.79	26.77	4.75			
1800	57 (13.9)	48.03	48.03	3.29	46.22	46.22	3.59	44.28	44.28	3.94	42.17	42.17	4.34	39.85	39.85	4.80			
	62 (16.7)	48.09	48.09	3.29	46.28	46.28	3.59	44.34	44.34	3.94	42.22	42.22	4.34	39.90	39.90	4.80			
	63 (17.2)††	47.93	39.06	3.29	45.73	38.10	3.59	43.42	37.10	3.94	40.94	36.03	4.34	38.28	34.85	4.78			
	67 (19.4)	51.57	40.77	3.30	49.20	39.82	3.60	46.70	38.82	3.95	44.03	37.75	4.35	41.15	36.58	4.80			
	72 (22.2)	56.62	32.23	3.31	54.02	31.29	3.61	51.26	30.29	3.97	48.31	29.24	4.37	45.11	28.12	4.83			

See notes on page 16

# DETAILED COOLING CAPACITIES# CONTINUED

EVAPORATOR AIR		CONDENSER ENTERING AIR TEMPERATURES ° F (° C)																	
		75 (23.9)			85 (29.4)			95 (35)			105 (40.6)			115 (46.1)			125 (51.7)		
		CFM	EWB ° F (° C)	Capacity MBtuh		Total System KW**	Capacity MBtuh		Total System KW**	Capacity MBtuh		Total System KW**	Capacity MBtuh		Total System KW**	Capacity MBtuh		Total System KW**	
Total	Sens†			Total	Sens†		Total	Sens†		Total	Sens†		Total	Sens†		Total	Sens†		
<b>114CNC060-A Outdoor Section With CAP**6024AL * Indoor Section</b>																			
	57 (13.9)	57.13	57.13	55.13	52.98	4.20	52.98	52.98	4.64	50.62	50.62	5.15	48.02	48.02	5.72	45.10	45.10	6.36	
<b>1750</b>	62 (16.7)	58.66	54.17	56.19	51.69	4.21	51.69	51.69	4.64	50.83	50.22	5.15	48.08	48.08	5.72	45.16	45.16	6.36	
	63 (17.2)††	59.58	44.09	57.01	41.69	4.21	41.69	41.69	4.65	51.27	40.38	5.15	48.03	38.97	5.72	44.47	37.42	6.35	
	67 (19.4)	64.25	45.85	61.48	44.68	4.24	44.68	43.44	4.68	52.28	42.12	5.19	51.78	40.71	5.76	47.95	39.17	6.39	
	72 (22.2)	70.70	37.43	67.65	36.25	4.27	36.25	35.01	4.72	60.83	33.69	5.23	56.96	32.28	5.80	52.74	30.74	6.44	
	57 (13.9)	59.42	59.42	57.27	54.97	4.31	54.97	54.97	4.75	52.44	52.44	5.26	49.65	49.65	5.83	46.55	46.55	6.47	
<b>2000</b>	62 (16.7)	60.03	58.04	57.54	55.03	4.31	55.03	55.03	4.75	52.50	52.50	5.26	49.71	49.71	5.83	46.60	46.60	6.48	
	63 (17.2)††	60.69	46.79	57.99	45.60	4.31	45.60	44.35	4.75	52.03	43.01	5.25	48.68	41.56	5.82	45.02	39.97	6.46	
	67 (19.4)	65.42	48.75	62.50	47.56	4.34	47.56	46.30	4.78	56.07	44.96	5.29	52.44	43.51	5.86	48.50	41.93	6.50	
	72 (22.2)	71.94	39.24	68.74	36.04	4.37	36.04	35.44	4.82	61.63	35.44	5.33	57.63	33.99	5.90	53.26	32.43	6.54	
	57 (13.9)	61.31	61.31	59.03	56.59	4.41	56.59	56.59	4.85	53.92	53.92	5.36	50.97	50.97	5.94	47.70	47.70	6.58	
<b>2250</b>	62 (16.7)	61.35	61.35	59.11	56.66	4.41	56.66	56.66	4.86	53.98	53.98	5.36	51.03	51.03	5.94	47.75	47.75	6.58	
	63 (17.2)††	61.52	49.35	58.74	46.15	4.41	46.15	46.86	4.85	52.61	45.49	5.35	49.17	43.99	5.92	45.44	42.32	6.56	
	67 (19.4)	66.26	51.51	63.27	50.31	4.43	50.31	49.03	4.88	56.65	47.65	5.39	52.93	46.16	5.96	48.91	44.47	6.59	
	72 (22.2)	72.86	40.94	69.55	39.73	4.46	39.73	38.45	4.91	62.20	37.07	5.43	58.08	35.61	6.00	53.59	34.03	6.64	

† Total and sensible capacities are net capacities. Blower motor heat has been subtracted.

‡ Sensible capacities shown are based on 80°F (27°C) entering air at the indoor coil. For sensible capacities at other than 80°F (27°C), deduct 835 Btuh (245 kW) per 1000 CFM (480 L/S) of indoor coil air for each degree below 80°F (27°C), or add 835 Btuh (245 kW) per 1000 CFM (480 L/S) of indoor coil air per degree above 80°F (27°C).

# Detailed cooling capacities are based on indoor and outdoor unit at the same elevation per AHRI standard 210/240-2008. If additional tubing length and/or indoor unit is located above outdoor unit, a slight variation in capacity may occur.

\*\* System kw is total of indoor and outdoor unit kilowatts.

†† At TVA rating indoor condition (75°F db/63°F wb). All other indoor air temperatures are at 80°F db.

NOTE: When the required data falls between the published data, interpolation may be performed. Extrapolation is not an acceptable practice.

EWB — Entering Wet Bulb



# CONDENSER ONLY RATINGS

SST ° F (° C)		CONDENSER ENTERING AIR TEMPERATURES ° F (° C)							
		55 (12.78)	65 (18.33)	75 (23.89)	85 (29.44)	95 (35.0)	105 (40.56)	115 (46.11)	125 (51.67)
<b>114CNC018-A</b>									
30 (-1.11)	TCG	15.60	14.50	13.50	12.60	11.70	10.70	9.70	8.70
	SDT	69.20	78.40	87.70	97.10	106.40	115.80	125.10	134.40
	KW	0.80	0.91	1.02	1.15	1.30	1.46	1.65	1.86
35 (1.67)	TCG	17.20	16.00	15.00	14.00	13.00	12.00	10.90	9.70
	SDT	70.40	79.60	88.90	98.20	107.50	116.80	126.00	135.10
	KW	0.80	0.91	1.02	1.16	1.30	1.47	1.65	1.87
40 (4.44)	TCG	18.80	17.60	16.50	15.40	14.40	13.30	12.10	10.90
	SDT	71.70	80.80	90.10	99.30	108.50	117.70	126.90	136.00
	KW	0.79	0.90	1.02	1.16	1.30	1.47	1.66	1.87
45 (7.22)	TCG	20.40	19.20	18.10	17.00	15.90	14.70	13.40	12.10
	SDT	73.00	82.10	91.20	100.40	109.60	118.70	127.80	136.90
	KW	0.78	0.90	1.02	1.15	1.30	1.47	1.66	1.88
50 (10.0)	TCG	22.20	21.00	19.80	18.60	17.40	16.10	14.80	13.40
	SDT	74.30	83.30	92.40	101.60	110.70	119.80	128.90	137.90
	KW	0.77	0.89	1.02	1.15	1.30	1.47	1.67	1.89
55 (12.78)	TCG	24.10	22.80	21.50	20.30	19.00	17.70	16.30	14.70
	SDT	75.60	84.60	93.70	102.80	111.90	121.00	130.00	138.90
	KW	0.76	0.88	1.01	1.15	1.30	1.48	1.67	1.89
<b>114CNC024-A</b>									
30 (-1.11)	TCG	21.10	19.90	18.70	17.60	16.40	15.20	14.10	12.80
	SDT	69.20	78.60	87.90	97.30	106.80	116.20	125.50	134.80
	KW	1.02	1.17	1.32	1.48	1.67	1.88	2.12	2.41
35 (1.67)	TCG	23.20	21.90	20.60	19.40	18.10	16.90	15.50	14.20
	SDT	70.50	79.80	89.10	98.40	107.80	117.00	126.30	135.60
	KW	1.03	1.17	1.32	1.49	1.67	1.88	2.13	2.41
40 (4.44)	TCG	25.40	24.00	22.70	21.30	20.00	18.60	17.10	15.60
	SDT	71.80	81.10	90.30	99.60	108.80	118.00	127.20	136.40
	KW	1.03	1.17	1.32	1.49	1.67	1.88	2.13	2.41
45 (7.22)	TCG	27.90	26.40	24.90	23.40	21.90	20.40	18.80	17.20
	SDT	73.30	82.40	91.50	100.70	109.90	119.00	128.10	137.20
	KW	1.03	1.18	1.33	1.49	1.67	1.89	2.13	2.41
50 (10.0)	TCG	30.40	28.80	27.30	25.70	24.00	22.40	20.60	18.80
	SDT	74.70	83.70	92.80	101.90	111.00	120.10	129.10	138.20
	KW	1.04	1.18	1.33	1.49	1.68	1.89	2.13	2.41
55 (12.78)	TCG	33.20	31.50	29.80	28.00	26.20	24.40	22.50	20.50
	SDT	76.20	85.20	94.20	103.20	112.20	121.20	130.20	139.20
	KW	1.04	1.18	1.33	1.49	1.68	1.89	2.13	2.41
<b>114CNC030-A</b>									
30 (-1.11)	TCG	24.90	23.60	22.30	20.90	19.60	18.20	16.70	15.20
	SDT	66.80	76.20	85.70	95.20	104.60	114.10	123.50	132.80
	KW	1.27	1.45	1.63	1.83	2.05	2.30	2.59	2.92
35 (1.67)	TCG	27.40	26.00	24.50	23.10	21.60	20.10	18.50	16.80
	SDT	68.00	77.30	86.70	96.20	105.60	114.90	124.20	133.50
	KW	1.28	1.45	1.64	1.83	2.05	2.30	2.59	2.93
40 (4.44)	TCG	30.10	28.60	27.00	25.40	23.80	22.10	20.40	18.60
	SDT	69.20	78.50	87.90	97.20	106.50	115.80	125.00	134.30
	KW	1.28	1.46	1.64	1.84	2.06	2.31	2.60	2.94
45 (7.22)	TCG	33.10	31.40	29.60	27.90	26.20	24.30	22.40	20.50
	SDT	70.60	79.80	89.10	98.30	107.50	116.70	125.90	135.10
	KW	1.29	1.47	1.65	1.84	2.06	2.31	2.60	2.95
50 (10.0)	TCG	36.20	34.40	32.50	30.60	28.70	26.70	24.60	22.40
	SDT	72.10	81.20	90.30	99.50	108.60	117.70	126.90	135.90
	KW	1.30	1.47	1.65	1.84	2.06	2.32	2.61	2.95
55 (12.78)	TCG	39.60	37.60	35.50	33.50	31.40	29.20	26.90	24.60
	SDT	73.60	82.60	91.60	100.70	109.80	118.80	127.90	136.80
	KW	1.30	1.47	1.65	1.85	2.07	2.32	2.61	2.96
<b>114CNC036-A</b>									
30 (-1.11)	TCG	31.10	28.80	26.90	25.20	23.60	21.80	19.90	17.80
	SDT	69.20	78.20	87.40	96.80	106.10	115.40	124.60	133.70
	KW	1.37	1.67	1.93	2.17	2.41	2.68	3.01	3.43
35 (1.67)	TCG	34.10	31.70	29.70	27.90	26.00	24.10	22.00	19.70
	SDT	70.50	79.50	88.70	97.90	107.10	116.30	125.50	134.50
	KW	1.34	1.66	1.92	2.16	2.40	2.68	3.01	3.42
40 (4.44)	TCG	37.30	34.80	32.70	30.70	28.70	26.60	24.20	21.70
	SDT	71.90	80.80	89.90	99.00	108.20	117.30	126.40	135.30
	KW	1.33	1.64	1.91	2.15	2.40	2.68	3.01	3.42
45 (7.22)	TCG	40.70	38.20	35.90	33.70	31.50	29.20	26.60	23.80
	SDT	73.40	82.20	91.30	100.30	109.40	118.40	127.40	136.20
	KW	1.31	1.63	1.90	2.15	2.40	2.68	3.02	3.43
50 (10.0)	TCG	44.50	41.80	39.40	37.00	34.60	31.90	29.10	26.00
	SDT	75.00	83.80	92.80	101.70	110.70	119.60	128.50	137.20
	KW	1.31	1.63	1.90	2.16	2.41	2.70	3.04	3.46
55 (12.78)	TCG	48.60	45.70	43.10	40.50	37.80	34.90	31.70	28.30
	SDT	76.80	85.50	94.40	103.30	112.10	120.90	129.60	138.20

See notes on page 18

# CONDENSER ONLY RATINGS CONTINUED

SST °F (°C)		CONDENSER ENTERING AIR TEMPERATURES °F (°C)							
		55 (12.78)	65 (18.33)	75 (23.89)	85 (29.44)	95 (35.0)	105 (40.56)	115 (46.11)	125 (51.67)
55 (12.78)	KW	1.32	1.64	1.92	2.18	2.44	2.73	3.07	3.49
<b>114CNC042-A</b>									
30 (-1.11)	TCG	36.20	34.20	32.30	30.50	28.70	26.70	24.60	22.20
	SDT	67.10	76.40	85.90	95.30	104.70	114.10	123.50	132.70
	KW	1.80	2.03	2.27	2.54	2.84	3.18	3.57	4.03
35 (1.67)	TCG	39.90	37.60	35.60	33.60	31.60	29.50	27.20	24.60
	SDT	68.40	77.60	86.90	96.30	105.60	114.90	124.20	133.40
	KW	1.83	2.05	2.29	2.55	2.85	3.19	3.58	4.05
40 (4.44)	TCG	43.80	41.40	39.10	36.90	34.70	32.40	29.90	27.10
	SDT	69.70	78.80	88.00	97.20	106.50	115.80	125.00	134.20
	KW	1.85	2.07	2.30	2.56	2.86	3.20	3.60	4.06
45 (7.22)	TCG	48.00	45.40	42.90	40.50	38.00	35.50	32.70	29.70
	SDT	71.00	80.00	89.10	98.30	107.50	116.70	125.90	135.00
	KW	1.87	2.08	2.31	2.57	2.87	3.21	3.61	4.07
50 (10.0)	TCG	52.50	49.60	46.90	44.20	41.60	38.80	35.80	32.50
	SDT	72.40	81.30	90.30	99.40	108.60	117.70	126.80	135.80
	KW	1.90	2.10	2.33	2.58	2.88	3.22	3.62	4.08
55 (12.78)	TCG	57.30	54.10	51.10	48.20	45.30	42.20	38.90	35.40
	SDT	73.90	82.70	91.60	100.60	109.70	118.70	127.70	136.60
	KW	1.93	2.12	2.34	2.60	2.89	3.23	3.63	4.09
<b>114CNC048-A</b>									
30 (-1.11)	TCG	41.60	39.40	37.20	35.00	32.70	30.40	27.90	25.20
	SDT	69.10	78.30	87.60	96.90	106.30	115.60	124.80	134.00
	KW	2.16	2.36	2.59	2.88	3.21	3.59	4.02	4.51
35 (1.67)	TCG	45.80	43.30	41.00	38.60	36.10	33.50	30.80	27.90
	SDT	70.50	79.60	88.80	98.10	107.30	116.50	125.70	134.80
	KW	2.17	2.37	2.61	2.89	3.23	3.61	4.05	4.54
40 (4.44)	TCG	50.20	47.60	45.00	42.40	39.80	36.90	34.00	30.70
	SDT	71.90	81.00	90.10	99.30	108.40	117.60	126.70	135.70
	KW	2.18	2.38	2.62	2.91	3.25	3.63	4.07	4.56
45 (7.22)	TCG	55.00	52.20	49.40	46.60	43.60	40.60	37.30	33.80
	SDT	73.50	82.50	91.50	100.60	109.60	118.70	127.70	136.60
	KW	2.18	2.38	2.63	2.92	3.26	3.65	4.09	4.59
50 (10.0)	TCG	60.10	57.10	54.10	51.00	47.80	44.40	40.80	37.00
	SDT	75.20	84.00	93.00	102.00	110.90	119.90	128.80	137.60
	KW	2.18	2.39	2.64	2.94	3.28	3.68	4.12	4.61
55 (12.78)	TCG	65.70	62.40	59.10	55.70	52.20	48.50	44.50	40.40
	SDT	76.90	85.70	94.60	103.50	112.40	121.20	130.00	138.70
	KW	2.18	2.39	2.65	2.95	3.30	3.70	4.15	4.64
<b>114CNC060-A</b>									
30 (-1.11)	TCG	54.20	51.50	48.70	45.90	43.00	39.90	36.60	33.10
	SDT	71.00	80.30	89.60	98.90	108.20	117.50	126.60	135.70
	KW	2.72	2.99	3.31	3.69	4.13	4.63	5.21	5.86
35 (1.67)	TCG	59.70	56.70	53.70	50.70	47.50	44.20	40.60	36.70
	SDT	72.60	81.80	91.10	100.30	109.50	118.60	127.70	136.70
	KW	2.75	3.02	3.34	3.73	4.17	4.68	5.26	5.91
40 (4.44)	TCG	65.60	62.30	59.10	55.80	52.30	48.60	44.80	40.60
	SDT	74.30	83.40	92.60	101.70	110.80	119.90	128.90	137.80
	KW	2.77	3.05	3.38	3.77	4.21	4.73	5.31	5.97
45 (7.22)	TCG	71.90	68.40	64.80	61.20	57.40	53.40	49.20	44.70
	SDT	76.20	85.20	94.20	103.20	112.20	121.20	130.10	138.90
	KW	2.79	3.08	3.41	3.80	4.26	4.78	5.36	6.02
50 (10.0)	TCG	78.70	74.80	71.00	67.00	62.90	58.50	53.90	49.00
	SDT	78.10	87.00	95.90	104.80	113.80	122.60	131.40	140.10
	KW	2.81	3.10	3.44	3.84	4.30	4.83	5.42	6.08
55 (12.78)	TCG	85.90	81.70	77.50	73.20	68.60	63.90	58.90	53.50
	SDT	80.10	88.90	97.70	106.60	115.40	124.10	132.80	141.30
	KW	2.82	3.12	3.47	3.88	4.34	4.87	5.47	6.13

\* AHRI listing applies only to systems shown in Combination Ratings table.

**KW** - Outdoor Unit Kilowatts Only.

**SDT** - Saturated Temperature Leaving Compressor (°F)

**SST** - Saturated Temperature Entering Compressor (°F/°C)

**TCG** - Gross Cooling Capacity (1000 Btuh)

# GUIDE SPECIFICATIONS

## GENERAL

### System Description

Outdoor-mounted, air-cooled, split-system air conditioner unit suitable for ground or rooftop installation. Unit consists of a hermetic compressor, an air-cooled coil, propeller-type condenser fan, and a control box. Unit will discharge supply air upward as shown on contract drawings. Unit will be used in a refrigeration circuit to match up to a packaged fan coil or coil unit.

### Quality Assurance

- Unit will be rated in accordance with the latest edition of AHRI Standard 210.
- Unit will be certified for capacity and efficiency, and listed in the latest AHRI directory.
- Unit construction will comply with latest edition of ANSI/ASHRAE and with NEC.
- Unit will be constructed in accordance with UL standards and will carry the UL label of approval. Unit will have c-UL-us approval.
- Unit cabinet will be capable of withstanding Federal Test Method Standard No. 141 (Method 6061) 500-hr salt spray test.
- Air-cooled condenser coils will be leak tested at 150 psig and pressure tested at 450 psig.
- Unit constructed in ISO9001 approved facility.

### Delivery, Storage, and Handling

- Unit will be shipped as single package only and is stored and handled per unit manufacturer's recommendations.

### Warranty (for inclusion by specifying engineer)

- U.S. and Canada only.

## PRODUCTS

### Equipment

Factory assembled, single piece, air-cooled air conditioner unit. Contained within the unit enclosure is all factory wiring, piping, controls, compressor, refrigerant charge Puron® (R-410A), and special features required prior to field start-up.

### Unit Cabinet

- Unit cabinet will be constructed of galvanized steel, bonderized, and coated with a powder coat paint.
- 3 phase equipment available with dense grille only.
- Single phase equipment available with wide (W) or dense (A) grille option.

## AIR-COOLED, SPLIT-SYSTEM AIR CONDITIONER

114CNC

1-1/2 TO 5 NOMINAL TONS

### Fans

- Condenser fan will be direct-drive propeller type, discharging air upward.
- Condenser fan motors will be totally enclosed, 1-phase type with class B insulation and permanently lubricated bearings. Shafts will be corrosion resistant.
- Fan blades will be statically and dynamically balanced.
- Condenser fan openings will be equipped with coated steel wire safety guards.

### Compressor

- Compressor will be hermetically sealed.
- Compressor will be mounted on rubber vibration isolators.

### Condenser Coil

- Condenser coil will be air cooled.
- Coil will be constructed of aluminum fins mechanically bonded to copper tubes which are then cleaned, dehydrated, and sealed.

### Refrigeration Components

- Refrigeration circuit components will include liquid-line shutoff valve with sweat connections, vapor-line shutoff valve with sweat connections, system charge of Puron® (R-410A) refrigerant, and compressor oil.
- Unit will be equipped with high-pressure switch, low pressure switch and filter drier for Puron refrigerant.

### Operating Characteristics

- The capacity of the unit will meet or exceed \_\_\_\_\_ Btuh at a suction temperature of \_\_\_\_\_ °F/°C. The power consumption at full load will not exceed \_\_\_\_\_ kW.
- Combination of the unit and the evaporator or fan coil unit will have a total net cooling capacity of \_\_\_\_\_ Btuh or greater at conditions of \_\_\_\_\_ CFM entering air temperature at the evaporator at \_\_\_\_\_ °F/°C wet bulb and \_\_\_\_\_ °F/°C dry bulb, and air entering the unit at \_\_\_\_\_ °F/°C.
- The system will have a SEER of \_\_\_\_\_ Btuh/watt or greater at DOE conditions.

### Electrical Requirements

- Nominal unit electrical characteristics will be \_\_\_\_\_ v, single phase, 60 hz. The unit will be capable of satisfactory operation within voltage limits of \_\_\_\_\_ v to \_\_\_\_\_ v.
- Unit electrical power will be single point connection.
- Control circuit will be 24v.

### Special Features

- Refer to section of this literature identifying accessories and descriptions for specific features and available enhancements.

## SYSTEM DESIGN SUMMARY

1. Intended for outdoor installation with free air inlet and outlet. Outdoor fan external static pressure available is less than 0.01-IN W.C.
2. Minimum outdoor operating air temperature without low-ambient operation accessory is 55°F (12.8°C).
3. Maximum outdoor operating air temperature is 125°F (51.7°C).
4. For reliable operation, unit should be level in all horizontal planes.
5. For interconnecting refrigerant tube lengths greater than 50 ft (15.2 m) and/or 20 ft (6.1 m) vertical differential, consult Residential Piping and Long Line Guideline and Service Manual available from equipment distributor.
6. If any refrigerant tubing is buried, provide a 6 in. (152.4 mm) vertical rise to the valve connections at the unit. Refrigerant tubing lengths up to 36 in. (914.4 mm) may be buried without further consideration. Do not bury refrigerant lines longer than 36 in. (914.4 mm).
7. Use only copper wire for electric connection at unit. Aluminum and clad aluminum are not acceptable for the type of connector provided.
8. Do not apply capillary tube indoor coils to these units.