

## Selection Guide

<b>30RAP (R-410A)</b>	011*	016*	018*	020*	025*	030*	035*	040*	045*	050*	055*
Capacity (tons)	10	14	16	19	23	28	34	39	43	47	52
Length (in.)	67	67	89	89	89	89	89	89	89	89	89
Approx. Weight (lb.)	762	800	1,125	1,133	1,242	1,283	2,163	2,185	2,238	2,263	2,369
<b>30RAP (R-410A) cont.</b>	060*	070	080	090	100	115	130	150			
Capacity (tons)	56	69	77	84	99	112	128	140			
Length (in.)	89	151	151	151	191	191	232	232			
Approx. Weight (lb.)	2,375	3,410	3,641	3,697	4,690	5,008	6,451	6,938			
<b>30RB (R-410A)</b>	060	070	080*	090*	100*	110*	120*	130*	150*	160*	170*
Capacity (tons)	57	67	76	86	93	106	118	127	140	153	164
Length (in.)	95	95	95	142	142	142	189	189	189	236	236
Approx. Weight (lb.)	3,783	3,978	4,267	5,449	5,663	6,027	7,119	7,402	8,517	9,475	9,799
<b>30RB (R-410A) cont.</b>	190*	210*	225*	250*	275*	300*	315*	330*	345*	360*	390*
Capacity (tons)	186	196	206	228	251	272	306	317	328	350	372
Length (in.)	283	283	283	330	377	424	472	472	472	519	566
Approx. Weight (lb.)	11,064	12,772	13,093	14,349	15,647	16,893	18,950	19,274	19,598	20,863	22,128
<b>30XA (R-134a)</b>	080	090	100	110	120	140	160	180	200	220	240
Capacity (tons)	76	85	94	103	111	133	153	172	195	213	229
Length (in.)	142	189	189	189	189	236	236	283	283	330	330
Approx. Weight (lb.)	7,234	9,382	9,603	9,738	9,877	12,023	12,255	12,699	12,810	13,748	13,897
<b>30XA (R-134a) cont.</b>	260	280	300	325	350	400	450	500			
Capacity (tons)	251	269	288	307	325	385	428	459			
Length (in.)	377	377	377	424	424	471	518	518			
Approx. Weight (lb.)	15,720	15,878	16,141	17,467	17,659	23,038	24,901	25,167			
<b>30XA with Greenspeed Intelligence (R-134a)</b>	140	160	180	200	220	240	260	280	300	325	350
Capacity (tons)	132	150	169	190	212	225	251	266	281	304	321
Length (in.)	264	264	311	311	358	358	405	405	405	452	452
Approx. Weight (lb.)	11,653	11,885	13,585	13,696	14,634	14,783	16,797	16,955	17,218	18,735	18,927

\*Available with Greenspeed® Intelligence (optional)

## Benefits at a Glance

### For Building Owners & Managers

- Reduced operating costs
- Quiet operation
- Reliable operation
- Environmentally balanced refrigerant

### For Consulting Engineers

- Simple to select
- ASHRAE 90.1 compliant
- High efficiency
- Reduced energy consumption
- HFC refrigerants

### For Contractors

- Streamlined installation
- Reduced installation expenses
- Reliable performance
- Easy to start-up and operate
- Plug-and-play hydronics



United Technologies  
turn to the experts

1-800-CARRIER [carrier.com/commercial](http://carrier.com/commercial)

© Carrier Corporation 2016 Cat. no. 04-811-50047  
Manufacturer reserves the right to discontinue, or change at any time, specifications or designs, without notice and without incurring obligations.

# Aqua Series

## Air-Cooled Chillers

### 10 to 500 Tons



# Environmentally Balanced and Energy-Efficient Air-Cooled Chillers

**AQUASNAP®**

**AQUAFORCE®**

Leave it to Carrier to design chillers in ways you'll notice at the initial purchase, through installation and for years afterward. Our Aqua Series chillers install quickly and easily to save you time

and money. And the savings will continue to mount with lower operating costs due to Aqua Series' superior full- and part-load performance. Available in 10- to 500-ton chillers, the Aqua Series chillers come in two lines:

**AquaSnap®** chillers with HFC Puron® refrigerant (R-410A) provide excellent part-load performance in a compact package, while meeting or exceeding ASHRAE 90.1 minimum energy efficiency requirements. Now available with optional Greenspeed® Intelligence, from 10 to 390 tons, delivering a quieter and much more efficient unit with IPLV up to 17.9.

**AquaForce®** chillers with HFC-134a provide full- and part-load performances in a single chassis exceeding ASHRAE 90.1 standards. The AquaForce chillers are also available with Greenspeed Intelligence with IPLVs up to 18.1.

With environmentally balanced refrigerant, simple installation, superior efficiency and powerful controls, these units are ideal for both replacement and new construction projects.



## Environmental Leadership

Carrier was the first manufacturer to introduce non-ozone-depleting refrigerant — a full six years ahead of the competition — paving the way for the future. Once again, Carrier leads the way, being the first to use environmentally balanced refrigerant in air-cooled chillers. All of the energy-efficient AquaSnap chillers, from 10 to 390 tons, come standard

with Puron refrigerant and can be incorporated into Leadership in Energy and Environmental Design (LEED®) Green Building Rating System projects. Furthermore all of the AquaForce chillers utilize HFC-134a.

## Affordability/Installability

Aqua Series air-cooled chillers feature a compact, all-in-one package design. Aqua Series chillers are available with or without an integrated hydronics package in many sizes. If you choose the optional built-in hydronics package, you get an entire chilled-water system with the pump, circuit setter, strainer, required piping and freeze protection to -20°F. For installation convenience, all pump motors offer standard VFD (variable frequency drive) compatibility and most hydronic packages are available with a factory-installed VFD. This prepackaged design costs less than buying and installing the components individually. The Aqua Series also saves on installed cost due to its rugged base frame. The frame is capable of point loading, which lowers installed cost by eliminating expensive field-erected base rails.

## Efficiency

Along with cost efficiency in purchase and installation, Aqua Series chillers are also more affordable to operate. They are highly efficient, with full-load energy efficiency ratios (EER) up to 10.9 and integrated part-load value (IPLV) ratings as high as 17.9. The key to Aqua Series chillers' great operating performance is the use of highly efficient rotary scroll and screw compressors. These compressors use patented sealing techniques, allowing for high volumetric efficiency and low frictional losses. They are maintenance-free and protected by an auto-adaptive control that minimizes wear.

## Quiet

Aqua Series chillers make their noise in the marketplace, not the workplace. The AquaSnap chiller's low-sound AeroAcoustic® fan produces up to half the sound level of the propeller fan. Much of the noise reduction is in frequencies where noise is most annoying, which makes AquaSnap chillers ideal for sound-sensitive environments. In addition, Aqua Series chillers offer a low-sound option.

LEED® is a registered trademark of the U.S. Green Building Council. AeroAcoustic® is a registered trademark of Aeroacoustic Corporation.



## AquaSnap® 30RAP Chillers

- 10 to 150 Tons
- HFC Puron® refrigerant (R-410A)
- Reduced operating costs
- Quiet operation
- Reliable operation
- Plug-and-play hydronics
- Novation® microchannel heat exchanger and round tube plate fin (070-150) coils
- With optional Greenspeed® Intelligence (010-060)
- IPLV up to 16.8



## AquaSnap® 30RB Scroll Chillers

- 60 to 390 Tons
- HFC Puron® refrigerant (R-410A)
- Simple to specify
- ASHRAE 90.1 compliant
- Streamlined installation
- Reduced installation expenses
- Plug-and-play hydronics
- Full heat recovery option
- With optional Greenspeed® Intelligence
- IPLV up to 17.1



## AquaForce® 30XA Screw Liquid Chillers

- 80 to 500 Tons
- HFC-134a refrigerant
- Reliable performance
- Easy to start up and operate
- High efficiency
- Reduced energy consumption
- Plug-and-play hydronics
- Direct expansion cooler option for low leaving fluid temperatures
- Greenspeed Intelligence version from 140 to 350 Tons
- IPLV up to 18.1
- Variable speed compressors and condenser fans

**SEISMICOMPLIANT**

Meets IBC 2006, ASCE-7-05, CBC 2007 and OSHPD seismic requirements.