


Job Name:	
Tag#	



Submittal Data Sheet	FTXM24VVJU / RXM24VVJU
2-Ton Wall Mounted Heat Pump System	



Efficiency			
Cooling		Heating	
SEER	22	HSPF	12.5
EER	12.5	COP	3.54

Performance	
Cooling (Btu/hr)	
Rated (Min/Max)	21,600 (9,000 / 26,000)
Sensible @ AHRI	16,200
Standard Operating Range	50°F – 114.8°F
Extended Operating Range*	-4°F – 114.8°F

Rated Cooling Conditions: Indoor: 80°F DB/67°F WB
Outdoor: 95°F DB/75°F WB

Heating (Btu/hr)	
1: @ 47° Rated (Min/Max)	24,000 (9,000 / 32,200)
2: @ 17° Rated	16,000
3: @ 5° Max: Capacity / COP	24,000 / 1.8
Operating Range	-13°F – 64.4°F

1: Rated Heating Conditions: Indoor: 70°F DB/60°F WB
Outdoor: 47°F DB/43°F WB

2: Rated Heating Conditions: Indoor: 70°F DB/60°F WB
Outdoor: 17°F DB/15°F WB

3: Heating Conditions; Compressor Operating at Max Frequency: Indoor: 70°F DB/60°F WB
Outdoor: 5°F DB/5°F WB

Electrical		
	208/60/1	230/60/1
System MCA	19.8	19.8
System MFA	20	20
Compressor RLA	19.25	19.25
Outdoor fan motor FLA	.58	.58
Outdoor fan motor W	123	123
Indoor fan motor FLA	.46	.46
Indoor fan motor W	61	61

MFA: Max. fuse amps **MCA:** Min. circuit amps (A) **FLA:** Full load amps (A)
RLA: Rated load amps (A) **W:** Fan motor rated output (W)

Piping	
Liquid (in)	1/4
Gas (in)	5/8
Drain (in)	5/8
Max. Interunit Piping Length (ft)	98.5
Max. Interunit Height Difference (ft)	82.02
Chargeless (ft)	49.2
Additional Charge of Refrigerant (oz/ft)	.22

Complete warranty details available from your local dealer or at www.daikincomfort.com. To receive the 12-Year Parts Limited Warranty, online registration must be completed within 60 days of installation. Online registration is not required in California or Quebec. If product is installed in a commercial application, limited warranty period is 5 years.

Indoor Specifications				
	Cooling		Heating	
	H	M	H	M
	Airflow Rate (cfm)	845	652	845
	L	SL	L	SL
	498	451	498	451
Sound (dBA) H / M / L / SL	51 / 44 / 37 / 34		51 / 42 / 37 / 34	
Dimensions (H × W × D) (in)	11-3/4 × 43-5/16 × 10-13/16			
Weight (Lbs)	33			

Outdoor Specifications				
Compressor	Hermetically Sealed Swing Type			
Refrigerant	R-32			
Factory Charge (Lbs)	2.98			
Refrigerant Oil	FW68DA			
	Cooling		Heating	
	H	SL	H	SL
	Airflow Rate (cfm)	2,179	1,833	2,119
Sound Pressure Level (dBA)	55 / 56			
Dimensions (H × W × D) (in)	28-15/16 × 34-1/4 × 12-5/8			
Weight (Lbs)	132			


Daikin North America LLC 5151 San Felipe, Suite 500 Houston, TX 77056

(Daikin's products are subject to continuous improvements. Daikin reserves the right to modify product design, specifications and information in this data sheet without notice and without incurring any obligations)

RXM24VVJU Dimensional Data



RXM24VVJU



3D107983A

Daikin North America LLC 5151 San Felipe, Suite 500 Houston, TX 77056

(Daikin's products are subject to continuous improvements. Daikin reserves the right to modify product design, specifications and information in this data sheet without notice and without incurring any obligations)

Submission Creation Date: August 2021

Page 3 of 4

Indoor Unit

Included	Part Number	Description
	AZAI6WSPDKC	DKN Plus Interface (Requires KER087A41)
	AZAI6WSCDKB	DKN Residential Cloud Wi-Fi Adaptor (Requires KER087A41)
	DTST-ONE-ADA-A	Daikin <i>One+</i> Smart Thermostat for Ductless Products (Requires KER087A41)
	BRC944B2	Wired Remote Controller (Requires KEP087A41)
	BRCW901A08	Wired Remote Controller Cable – 25ft
	BRCW901A03	Wired Remote Controller Cable – 10ft
	KAF970A46	Titanium apatite photocatalytic air-purifying filter WITHOUT frame
	DACA-CP1-1	Inline Condensate Pump (Fits inside all Daikin wall & floor mount units)
	DACA-CP4-1	External Condensate Pump
	KRP928BB2S	Interface Adaptor for DIII-NET (Requires KER087A41)
	KER087A41	S21 Conversion Connector

Outdoor Unit

Included	Part Number	Description
	DACA-WB-1	Powder-Coated Wall-Mounted Bracket
	KPW063B4	Air direction adjustment grille
	KEH063A4E(A)	Daikin BML Drain Pan Heater Large
	KKG063A42	Back protection wire net (15, 18 & 24)
	KPS063A41	Snow hood (intake side plate) (15, 18 & 24)
	KPS063A44	Snow hood (intake rear plate) (15,18 & 24)
	KPS063A47	Snow hood (outlet) (15, 18 & 24)
	KKP937A4	Drain Plug for OD Unit