


## PTAC PDE07K3SG

Cooling BTU: **7200/7000**  
Heating BTU: **11700/8300**  
EER: **13.0/13.0**

Volts: **230/208**



### Unit Dimensions

Height: **16"**  
Width: **42"**  
Depth: **13 3/4"**

### Additional Measurement Specs

Front Cover Height: **16"**  
Front Cover Width: **42"**  
Front Cover Depth: **7 3/4"**  
Cut-Out Height: **16 1/4"**  
Cut-Out Width: **42 1/4"**  
Dimensions With Package: **21 1/2"**  
Net Weight: **106 lbs**  
Shipping Weight: **126 lbs**

### Detailed Electrical Information



Voltage: **230/208**  
Volt Range: **253-187**  
Cooling Amps: **2.7/2.9**  
Cooling Watts: **550/535**  
Reverse Heating Amps: **15.0/13.6|10.7/9.7**  
Reverse Heating Watts: **3450/2450**  
Compressor LRA: **13**  
Compressor RLA: **2.5**

### Additional Performance Specs

Air Circulation: **300 CFM**  
Moisture Removal: **1.7 pints per hour**  
Indoor CFM High: **345**  
Indoor CFM Low: **315**  
Sensible Heat Ratio: **0.86**  
Vent CFM: **75**  
R-410A Charge: **23 oz**  
Suggested Retail Price: Please contact the Friedrich Contract Sales Department at (800) 541-6645