


PTAC PDE12K3SG

Cooling BTU: **11800/11600**
 Heating BTU: **17000/11700/8300**
 EER: **11.6/11.6**

Volts: **230/208**



Unit Dimensions

Height: **16"**
 Width: **42"**
 Depth: **13 3/4"**

Additional Measurement Specs

Front Cover Height: **16"**
 Front Cover Width: **42"**
 Front Cover Depth: **7 3/4"**
 Cut-Out Height: **16 1/4"**
 Cut-Out Width: **42 1/4"**
 Dimensions With Package: **21 1/2"**
 Net Weight: **119 lbs**
 Shipping Weight: **139 lbs**

Detailed Electrical Information



Voltage: **230/208**
 Volt Range: **253-187**
 Cooling Amps: **4.9/5.1**
 Cooling Watts: **1015/1000**
 Reverse Heating Amps: **21.8/19.7|15.0/13.6|10.7/9.7**
 Reverse Heating Watts: **5000/2450/2450**
 Compressor LRA: **21.5**
 Compressor RLA: **4.7**

Additional Performance Specs

Air Circulation: **300 CFM**
 Moisture Removal: **2.7 pints per hour**
 Indoor CFM High: **400**
 Indoor CFM Low: **390**
 Sensible Heat Ratio: **139**
 Vent CFM: **75**
 R-410A Charge: **36 oz**
 Suggested Retail Price: Please contact the Friedrich Contract Sales Department at (800) 541-6645