


PTAC PDE12R3SG

Cooling BTU: **11800**
 Heating BTU: **17000/11700/8300**
 EER: **11.6**

Volts: **265**



Unit Dimensions

Height: **16"**
 Width: **42"**
 Depth: **13 3/4"**

Additional Measurement Specs

Front Cover Height: **16"**
 Front Cover Width: **42"**
 Front Cover Depth: **7 3/4"**
 Cut-Out Height: **16 1/4"**
 Cut-Out Width: **42 1/4"**
 Dimensions With Package: **21 1/2"**
 Net Weight: **118 lbs**
 Shipping Weight: **138 lbs**

Detailed Electrical Information



Voltage: **265**
 Volt Range: **292-239**
 Cooling Amps: **4.2**
 Cooling Watts: **1015**
 Reverse Heating Amps: **18.87|13.02|9.25**
 Reverse Heating Watts: **5000/3450/2450**
 Compressor LRA: **19**
 Compressor RLA: **3.9**
 Power Cord Length: **18"**

Additional Performance Specs

Air Circulation: **300 CFM**
 Moisture Removal: **2.7 pints per hour**
 Indoor CFM High: **400**
 Sensible Heat Ratio: **0.75**
 Vent CFM: **75**
 R-410A Charge: **36 oz**
 Suggested Retail Price: Please contact the Friedrich Contract Sales Department at (800) 541-6645