


PTAC PDH07K3SG

Cooling BTU: **7200/7000**
 Heating BTU: **6000/5800**
 EER: **13.0**

Volts: **230/208**



Unit Dimensions

Height: **16"**
 Width: **42"**
 Depth: **13 3/4"**

Additional Measurement Specs

Front Cover Height: **16"**
 Front Cover Width: **42"**
 Front Cover Depth: **7 3/4"**
 Cut-Out Height: **16 1/4"**
 Cut-Out Width: **42 1/4"**
 Dimensions With Package: **21 1/2"**
 Net Weight: **113 lbs**
 Shipping Weight: **133 lbs**

Detailed Electrical Information



Voltage: **230/208**
 Volt Range: **253-187**
 Cooling Amps: **2.7/2.9**
 Cooling Watts: **550/535**
 Reverse Heating Amps: **2.6/2.4**
 Reverse Heating Watts: **485/470**
 Compressor LRA: **13**
 Compressor RLA: **2.5**

Additional Performance Specs

Air Circulation: **300 CFM**
 COP: **3.6/3.6**
 Moisture Removal: **1.7 pints per hour**
 Indoor CFM High: **345**
 Indoor CFM Low: **315**
 Sensible Heat Ratio: **0.86**
 Vent CFM: **75**
 R-410A Charge: **34 oz**
 Suggested Retail Price: Please contact the Friedrich Contract Sales Department at (800) 541-6645