

INDOOR UNIT SPECIFICATION

# 4 Way CASSETTE (570 × 570)

ARNU05GTRD4 / ARNU07GTRD4 / ARNU09GTRD4 / ARNU12GTRD4  
ARNU15GTQD4 / ARNU18GTQD4 / ARNU21GTQD4



Model	Independent Unit		ARNU05GTRD4	ARNU07GTRD4	ARNU09GTRD4	ARNU12GTRD4	ARNU15GTQD4	ARNU18GTQD4	ARNU21GTQD4
Capacity	Cooling	Nom kW	1.6	2.2	2.8	3.6	4.5	5.6	6.0
	Heating	Nom kW	1.8	2.5	3.2	4.0	5.0	6.3	6.8
Power Input	Cooling / Heating	Nom <sup>1)</sup> W	13	13	14	17	24	25	28
	Cooling / Heating	Rated <sup>2)</sup> W	30	30	30	30	30	30	30
Power Supply		Ø/V/Hz	1 / 220-240 / 50 1 / 220 / 60	1 / 220-240 / 50 1 / 220 / 60	1 / 220-240 / 50 1 / 220 / 60	1 / 220-240 / 50 1 / 220 / 60	1 / 220-240 / 50 1 / 220 / 60	1 / 220-240 / 50 1 / 220 / 60	1 / 220-240 / 50 1 / 220 / 60
Airflow Rate	Cooling	H / M / L m <sup>3</sup> /min	7.5 / 7.0 / 6.6	7.5 / 7.0 / 6.6	8.0 / 7.5 / 7.1	8.7 / 8.0 / 7.0	11.0 / 10.0 / 9.3	11.2 / 11.0 / 10.0	12.0 / 11.1 / 9.4
	Heating	H / M / L m <sup>3</sup> /min	7.5 / 7.0 / 6.6	7.5 / 7.0 / 6.6	8.0 / 7.5 / 7.1	8.7 / 8.0 / 7.0	11.0 / 10.0 / 9.3	11.2 / 11.0 / 10.0	12.0 / 11.1 / 9.4
Sound Pressure		H / M / L dBA	29 / 27 / 26	29 / 27 / 26	30 / 29 / 27	32 / 30 / 27	36 / 34 / 32	37 / 35 / 34	40 / 38 / 34
Sound Power		H / M / L dBA	46 / 44 / 43	46 / 44 / 43	47 / 46 / 44	48 / 47 / 44	51 / 49 / 47	52 / 50 / 49	55 / 53 / 49
Dimensions	Body	W x H x D mm	570 x 214 x 570	570 x 214 x 570	570 x 214 x 570	570 x 214 x 570	570 x 256 x 570	570 x 256 x 570	570 x 256 x 570
Net Weight		kg	12.6	12.6	13.7	13.7	15.0	15.0	15.0
Piping Connection	Liquid	mm	6.35	6.35	6.35	6.35	6.35	6.35	9.52
	Gas	mm	12.7	12.7	12.7	12.7	12.7	12.7	15.88
	Drain	ID mm	25.0	25.0	25.0	25.0	25.0	25.0	25.0
Decoration Panel 1	Model		PT-UQC	PT-UQC	PT-UQC	PT-UQC	PT-UQC	PT-UQC	PT-UQC
	Color (RAL Code)		Morning Fog (RAL 120-4)	Morning Fog (RAL 120-4)	Morning Fog (RAL 120-4)	Morning Fog (RAL 120-4)	Morning Fog (RAL 120-4)	Morning Fog (RAL 120-4)	Morning Fog (RAL 120-4)
	Dimensions	W x H x D mm	700 x 22 x 700	700 x 22 x 700	700 x 22 x 700	700 x 22 x 700	700 x 22 x 700	700 x 22 x 700	700 x 22 x 700
	Weight	kg	3.0	3.0	3.0	3.0	3.0	3.0	3.0
Decoration Panel 2	Model		PT-QCHW0	PT-QCHW0	PT-QCHW0	PT-QCHW0	PT-QCHW0	PT-QCHW0	PT-QCHW0
	Color (RAL Code)		Morning Fog (RAL 120-4)	Morning Fog (RAL 120-4)	Morning Fog (RAL 120-4)	Morning Fog (RAL 120-4)	Morning Fog (RAL 120-4)	Morning Fog (RAL 120-4)	Morning Fog (RAL 120-4)
	Dimensions	W x H x D mm	620 x 35 x 620	620 x 35 x 620	620 x 35 x 620	620 x 35 x 620	620 x 35 x 620	620 x 35 x 620	620 x 35 x 620
	Weight	kg	3.1	3.1	3.1	3.1	3.1	3.1	3.1

\* This product contains Fluorinated Greenhouse Gases. (R410A)

1) Nom. : Performance tested under EN14511

2) Rated : Max power input allowed for fan motor

Note : 1. Capacities are based on the following conditions

- Cooling : Indoor temp. 27°C (80.6°F) DB / 19°C (66.2°F) WB, Outdoor temp. 35°C (95°F) DB / 24°C (75.2°F) WB, Interconnecting piping length 7.5m, Level difference of zero
- Heating : Indoor temp. 20°C (68°F) DB / 15°C (59°F) WB, Outdoor temp. 7°C (44.6°F) DB / 6°C (42.8°F) WB, Interconnecting piping length 7.5m, Level difference of zero

2. Due to our policy of innovation some specifications may be changed without notification 3. I.D. : ' Internal Diameter '

## Accessories

Model	ARNU05GTRD4	ARNU07GTRD4	ARNU09GTRD4	ARNU12GTRD4	ARNU15GTQD4	ARNU18GTQD4	ARNU21GTQD4
Dry Contact	Simple (1 Contact Point with Case)			PDRYCB000			
	2 Contact Point			PDRYCB400			
	For Thermostat (On-Off / Mode / Fan Speed)			PDRYCB300			
	Modbus Communication			PDRYCB500			
Front Panel	PT-QCHW0 / PT-UQC						
Ventilation Kit	PTVK430						
EEV Kit for MULTI V Indoor	PRGK024A0						

Wired Remote Controller							Wireless Remote Controller
Premium	Standard III		Standard II		Simple	Simple for Hotel	
PREMTA000 PREMTA000A PREMTA000B	PREMTB100 (White)	PREMTBB10 (Black)	PREMTB001 (White)	PREMTBB01 (Black)	PQRCVCLQ (Black) PQRCVCLQW (White)	PQRCHCA0Q (Black) PQRCHCA0QW (White)	PQWRHQ0FDB

INDOOR UNIT SPECIFICATION

# 4 Way CASSETTE (840 × 840)

ARNU24GTPC4 / ARNU28GTPC4 / ARNU30GTPC4 / ARNU36GTNC4  
ARNU42GTMC4 / ARNU48GTMC4 / ARNU54GTMC4



Model	Independent Unit		ARNU24GTPC4	ARNU28GTPC4	ARNU30GTPC4	ARNU36GTNC4	ARNU42GTMC4	ARNU48GTMC4	ARNU54GTMC4
Capacity	Cooling	Nom kW	7.1	8.2	9.0	10.6	12.3	14.1	15.8
	Heating	Nom kW	8.0	9.2	10.0	11.9	13.8	15.9	18.0
Power Input	Cooling / Heating	Nom <sup>1)</sup> W	31	40	40	70	104	120	135
	Cooling / Heating	Rated <sup>2)</sup> W	40	40	40	144	144	144	144
Power Supply		Ø/V/Hz	1 / 220-240 / 50 1 / 220 / 60	1 / 220-240 / 50 1 / 220 / 60	1 / 220-240 / 50 1 / 220 / 60	1 / 220-240 / 50 1 / 220 / 60	1 / 220-240 / 50 1 / 220 / 60	1 / 220-240 / 50 1 / 220 / 60	1 / 220-240 / 50 1 / 220 / 60
Airflow Rate	Cooling	H / M / L m <sup>3</sup> /min	17.0 / 15.0 / 13.0	19.0 / 16.0 / 14.0	24.3 / 22.8 / 19.5	25.0 / 21.0 / 19.0	30.0 / 27.0 / 24.0	31.0 / 29.0 / 27.0	34.0 / 32.0 / 27.0
	Heating	H / M / L m <sup>3</sup> /min	17.0 / 15.0 / 13.0	19.0 / 16.0 / 14.0	24.3 / 22.8 / 19.5	25.0 / 21.0 / 19.0	30.0 / 27.0 / 24.0	31.0 / 29.0 / 27.0	34.0 / 32.0 / 27.0
Sound Pressure		H / M / L dBA	36 / 34 / 31	39 / 35 / 33	40 / 36 / 33	43 / 40 / 37	44 / 41 / 38	46 / 43 / 41	50 / 48 / 44
Sound Power		H / M / L dBA	55 / 53 / 50	56 / 54 / 52	57 / 54 / 52	62 / 59 / 56	63 / 59 / 56	65 / 61 / 59	69 / 67 / 63
Dimensions	Body	W x H x D mm	840 x 204 x 840	840 x 204 x 840	840 x 204 x 840	840 x 246 x 840	840 x 288 x 840	840 x 288 x 840	840 x 288 x 840
Net Weight		kg	20.8	20.8	20.8	23.5	25.6	25.6	26.5
Piping Connection	Liquid	mm	9.52	9.52	9.52	9.52	9.52	9.52	9.52
	Gas	mm	15.88	15.88	15.88	15.88	15.88	15.88	15.88
	Drain	ID mm	25.0	25.0	25.0	25.0	25.0	25.0	25.0
Decoration Panel 1	Model		PT-UMC1	PT-UMC1	PT-UMC1	PT-UMC1	PT-UMC1	PT-UMC1	PT-UMC1
	Color (RAL Code)		Morning Fog (RAL 120-4)	Morning Fog (RAL 120-4)	Morning Fog (RAL 120-4)	Morning Fog (RAL 120-4)	Morning Fog (RAL 120-4)	Morning Fog (RAL 120-4)	Morning Fog (RAL 120-4)
	Dimensions	W x H x D mm	950 x 25 x 950	950 x 25 x 950	950 x 25 x 950	950 x 25 x 950	950 x 25 x 950	950 x 25 x 950	950 x 25 x 950
	Weight	kg	5.6	5.6	5.6	5.6	5.6	5.6	5.6
Decoration Panel 2	Model		PT-MCHW0	PT-MCHW0	PT-MCHW0	PT-MCHW0	PT-MCHW0	PT-MCHW0	PT-MCHW0
	Color (RAL Code)		Morning Fog (RAL 120-4)	Morning Fog (RAL 120-4)	Morning Fog (RAL 120-4)	Morning Fog (RAL 120-4)	Morning Fog (RAL 120-4)	Morning Fog (RAL 120-4)	Morning Fog (RAL 120-4)
	Dimensions	W x H x D mm	950 x 35 x 950	950 x 35 x 950	950 x 35 x 950	950 x 35 x 950	950 x 35 x 950	950 x 35 x 950	950 x 35 x 950
	Weight	kg	6.3	6.3	6.3	6.3	6.3	6.3	6.3

\* This product contains Fluorinated Greenhouse Gases. (R410A)

1) Nom. : Performance tested under EN14511

2) Rated : Max power input allowed for fan motor

Note : 1. Capacities are based on the following conditions

- Cooling : Indoor temp. 27°C (80.6°F) DB / 19°C (66.2°F) WB, Outdoor temp. 35°C (95°F) DB / 24°C (75.2°F) WB, Interconnecting piping length 7.5m, Level difference of zero
- Heating : Indoor temp. 20°C (68°F) DB / 15°C (59°F) WB, Outdoor temp. 7°C (44.6°F) DB / 6°C (42.8°F) WB, Interconnecting piping length 7.5m, Level difference of zero

2. Due to our policy of innovation some specifications may be changed without notification 3. I.D. : ' Internal Diameter '

## Accessories

Model	ARNU24GTPC4	ARNU28GTPC4	ARNU30GTPC4	ARNU36GTNC4	ARNU42GTMC4	ARNU48GTMC4	ARNU54GTMC4
Dry Contact	Simple (1 Contact Point with Case)			PDRYCB000			
	2 Contact Point			PDRYCB400			
	For Thermostat (On-Off / Mode / Fan Speed)			PDRYCB300			
	Modbus Communication			PDRYCB500			
Front Panel	PT-UMC1 / PT-MCHW0						
Ventilation Kit	PTEGMO						
EEV Kit for MULTI V Indoor	PTVK410 / PTVK420 / PTVK430						

Wired Remote Controller							Wireless Remote Controller
Premium	Standard III		Standard II		Simple	Simple for Hotel	
PREMTA000 PREMTA000A PREMTA000B	PREMTB100 (White)	PREMTBB10 (Black)	PREMTB001 (White)	PREMTBB01 (Black)	PQRCVCLQ (Black) PQRCVCLQW (White)	PQRCHCA0Q (Black) PQRCHCA0QW (White)	PQWRHQ0FDB